

# BTK

# タップド ブラインド ノブ

標準 在庫品

RHS

SUS

材質の特性  
P.2231

追加加工

ネジ  
カット

ネジ  
組付け  
P.2200~

Original ELESA Model VC.192



elesta




(メネジ)



(オネジ)



(メネジ)



(オネジ)

★One Point  
フラット形状で汚れにくい

タイプ	ノブ	メネジ	オネジ
BTK	フェノール樹脂 光沢仕上げ	黄銅 (カドミウム低減材)	S10C 亜鉛メッキ
BTK-SUS	ブラック	SUS303	SUS303

## ■メネジ

黄銅製		SUS製		D	M	H	D <sub>1</sub>	S	Lf
品番	質量(g)	品番	質量(g)						
BTK25	11	—	—	25	M 4×0.7	21	15	9	10
BTK30A	16	—	—	32	M 5×0.8	23	19	11	
BTK30B	19	BTK30-SUS	18		M 6×1				27
BTK40A	27	—	—	40	M 8×1.25	33	25	14	
BTK40B	31	BTK40-SUS	30						50
BTK50A	50	—	—	60	M12×1.75	44	30	20	
BTK50B	52	BTK50-SUS	50						70
BTK60A	76	—	—	85					
BTK60B	80	BTK60-SUS	78						
BTK70	119	—	—						
BTK85	176	—	—						

## ■オネジ

		スチール製		SUS製		D	M	H	D <sub>1</sub>	S	L
品番	質量(g)	品番	質量(g)	品番	質量(g)						
EA948AD-101	BTK25 ×10	11	—	—	—	25	M 5×0.8	21	15	9	10
EA948AD-102	BTK25 ×16	12	—	—	—						16
EA948AD-103	BTK25A×10	10	—	—	—						10
EA948AD-104	BTK25A×16	12	—	—	—		16				
EA948AD-105	BTK25A×20	14	—	—	—		20				
EA948AD-106	BTK25A×30	18	—	—	—		30				
EA948AD-107	BTK30 ×10	17	BTK30×10-SUS	17	—		32				M 6×1
	BTK30 ×16	18	BTK30×16-SUS	18	—	16					
	BTK30 ×20	20	BTK30×20-SUS	20	—	20					
EA948AD-110	BTK30 ×35	25	BTK30×35-SUS	25	—	35					
EA948AD-111	BTK30A×20	24	—	—	—	20					
EA948AD-112	BTK30A×30	27	—	—	—	30					
EA948AD-113	BTK30A×40	29	—	—	—	40					
EA948AD-114	BTK40A×20	30	—	—	—	40	M 6×1	27	21	12	20
EA948AD-115	BTK40A×30	32	—	—	—						30
	BTK40 ×16	35	—	—	—						16
	—	—	BTK40×20-SUS	36	—		20				
EA948AD-117	BTK40 ×25	38	BTK40×25-SUS	38	—		25				
	—	—	BTK40×30-SUS	39	—		30				
EA948AD-118	BTK40 ×35	40	BTK40×35-SUS	40	—		35				
	BTK40 ×45	43	BTK40×45-SUS	43	—	45					
EA948AD-120	BTK50A×16	52	—	—	—	50	M 8×1.25	33	25	14	16
EA948AD-121	BTK50A×20	53	—	—	—						20
EA948AD-122	BTK50A×25	55	—	—	—						25
EA948AD-123	BTK50A×30	56	—	—	—		30				
	BTK50A×40	60	—	—	—		40				
	BTK50 ×20	63	BTK50×20-SUS	63	—		20				
	BTK50 ×30	66	BTK50×30-SUS	66	—		30				
EA948AD-127	BTK50 ×40	70	BTK50×40-SUS	70	—	60	M10×1.5	37	27	17	40
EA948AD-128	BTK50 ×50	73	BTK50×50-SUS	73	—						50
	BTK60 ×20	87	—	—	—						20
	BTK60 ×30	92	—	—	—		30				
EA948AD-131	BTK60 ×40	98	—	—	—		40				
EA948AD-132	BTK60 ×50	101	—	—	—		50				
EA948AD-133	BTK60 ×25B	105	—	—	—		25				
EA948AD-134	BTK60 ×30B	110	BTK60×30-SUS	110	—	M12×1.75					30
EA948AD-135	BTK60 ×40B	118	BTK60×40-SUS	118	—						40
EA948AD-136	BTK60 ×50B	128	BTK60×50-SUS	128	—						50

### 特長

- ・SUS製はネジ部にSUSを用いた製品で、食品機械、衛生機器に最適です。
- ・フラット形状で汚れにくいです。

### 技術データ

使用温度 max.110℃ min.-20℃

追加加工を承ります!

