



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : KUKKO Special grease
Product code : 699999

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricants and lubricant additives

1.3 Details of the supplier of the safety data sheet

KUKKO Werkzeugfabrik Kleinbongartz & Kaiser oHG
Heinrich-Hertz-Str. 5
40721 Hilden • GERMANY
Phone: +49 2103 9754-300
www.KUKKO.com • info@kukko.com

1.4 Emergency telephone number

Phone: +49 (0)551 19240

SECTION 2: Hazards identification


2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements : **Prevention:**
P280 Wear eye protection/ face protection.



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Hazardous components which must be listed on the label:

Calcium hydroxide

Additional Labelling:

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Inorganic and organic compounds dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5 265-155-0	Asp. Tox. 1; H304	>= 20 - < 30
Calcium hydroxide	1305-62-0 215-137-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335	>= 3 - < 5
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0 274-263-7	Skin Sens. 1; H317	>= 0.1 - < 1

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May produce an allergic reaction.
Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Formaldehyde

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures



KUKKO Special grease (Art.No.: 699999)

Version Revision Date:
1.4 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice.
Keep container tightly closed.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Keep tightly closed. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Calcium hydroxide	1305-62-0	TWA	5 mg/m ³	91/322/EEC
Further information	Existing scientific data on health effects appear to be particularly limited, Indicative			
		TWA	5 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium hydroxide	Workers	Inhalation	Acute local effects	4 mg/m ³
	Workers	Inhalation	Long-term local effects	1 mg/m ³
	Consumers	Inhalation	Acute local effects	4 mg/m ³
	Consumers	Inhalation	Long-term local effects	1 mg/m ³
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	Workers	Inhalation	Long-term systemic effects	0.66 mg/m ³
	Workers	Skin contact	Long-term systemic effects	3.33 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.33 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	1.667 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.8333 mg/kg bw/day



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Residual oils (petroleum), solvent-dewaxed	Oral	9.33 mg/kg
Calcium hydroxide	Fresh water	0.49 mg/l
	Marine water	0.32 mg/l
	Intermittent use/release	0.49 mg/l
	Sewage treatment plant	3 mg/l
	Soil	1080 mg/kg
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	Fresh water	1 mg/l
	Marine water	1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	723500000 mg/kg
	Marine sediment	723500000 mg/kg
	Soil	16.667 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

- Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield
- Hand protection
Material : Impervious gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Grease

Colour : black

Odour : slight

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : ≥ 220 °C
Method: closed cup

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : Not applicable

Relative vapour density : No data available

Relative density : 0.9

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Viscosity
Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Calcium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials



KUKKO Special grease (Art.No.: 699999)

Version 1.4 Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Calcium hydroxide:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Skin irritation

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Rabbit
Result: No eye irritation
Remarks: Based on data from similar materials

Calcium hydroxide:

Species: Rabbit
Method: OECD Test Guideline 405
Result: Irreversible effects on the eye

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Species: Rabbit
Method: Draize Test
Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Result: negative
Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Assessment: Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Calcium hydroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Calcium hydroxide:

Species: Rat
Application Route: Ingestion
Exposure time: 104 weeks
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

Calcium hydroxide:
Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:
Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 415
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure
Not classified based on available information.

Components:

Calcium hydroxide:
Assessment: May cause respiratory irritation.
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

STOT - repeated exposure
Not classified based on available information.

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:
Species: Rat
NOAEL: > 0.98 mg/l
Application Route: inhalation (dust/mist/fume)
Exposure time: 28 Days
Remarks: Based on data from similar materials

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:
Species: Rat
NOAEL: 500 mg/kg



KUKKO Special grease (Art.No.: 699999)

Version 1.4 Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Application Route: Ingestion
Exposure time: 29 d
Method: OECD Test Guideline 407

Species: Rat
NOAEL: > 1,000 mg/kg
Application Route: Skin contact
Exposure time: 28 d
Method: OECD Test Guideline 410
Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC : > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on data from similar materials

Calcium hydroxide:

Toxicity to fish : LC50 (Gasterosteus aculeatus (threespine stickleback)): 457 mg/l
Exposure time: 96 h



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 49.1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae : EC10 (Pseudokirchneriella subcapitata (green algae)): 79.22 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- EC50 (Pseudokirchneriella subcapitata (green algae)): 184.57 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to bacteria : EC50 : 300.4 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
Exposure time: 14 d

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

- Toxicity to fish : LL50 (Cyprinodon variegatus (sheepshead minnow)): > 10,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Benzenesulfonic acid, mono-C16-24-alkyl derivs.,calcium salts:

- Biodegradability : Result: Not readily biodegradable.



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Biodegradation: 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t

The components of this product are reported in the following inventories:

TSCA : Clearance for manufacture, import, processing, or use of this product under the United States Toxic Substances Control Act (TSCA) is based on a low volume exemption (LVE) from the Inventory listing requirements of TSCA (40 CFR 723.50(c) (1)).

REACH : All ingredients (pre-)registered or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : Consult your local Dow Corning office.

DSL : This product contains one or more substances which are not on the Canadian Domestic Substances List (DSL). Import of this product into Canada has volume limitations. For volume limits please consult Dow Corning Regulatory Compliance.

Additional regulatory information



KUKKO Special grease (Art.No.: 699999)

Version 1.4
Revision Date: 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

9-Octadecenyl-13-docosenate 17673-56-2

TSCA clearance for manufacture, import, processing, or use of this product is based on a low volume exemption from the Inventory listing requirements of TSCA (40 CFR 723.50(c) (1)). For activities regulated by TSCA, the following conditions apply: The LVE substance contained in the product may only be used as a lubricant. The low volume exemption specifies that processors and industrial users of this product will control exposure by using pumping and application apparatus for transfer and use whenever possible, and will landfill spent product containers.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT SE : Specific target organ toxicity - single exposure
91/322/EEC : Europe. Commission Directive 91/322/EEC on establishing indicative limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
91/322/EEC / TWA : Limit Value - eight hours
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New



KUKKO Special grease (Art.No.: 699999)

Version Revision Date:
1.4 10.10.2015

Date of last issue: 30.09.2015
Date of first issue: 03.12.2014

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN