

Date of first issue 1997/01/10

Date of revised 2019/08/13

SAFETY DATA SHEET

1 . IDENTIFICATION

Name of chemical substances: WATER-BASED AQUEOUS MULTIPURPOSE PAINT YELLOW
 Kinds of product: Acrylic resins emulsion paint
 Company name: SUNDAY PAINT Co., Ltd
 Address: 6F SR Building NAGAHORI, 1-18-11, MINAMISEMBA, CHUO-KU, OSAKA 542-0081 Japan
 Section in charge: Mayor of customer service
 Phone number: +81-6-6266-3150
 FAX number: +81-6-6266-3146
 Emergency telephone number: +81-6-6266-3150
 Reference number: 300384
 Use: For general

2 . HAZARDS IDENTIFICATION

GHS classification:

Physicochemical Hazards:

Explosives	: Classification not possible
Flammable gases	: Not applicable
Flammable aerosols	: Not applicable
Oxidizing gases	: Not applicable
Gases under pressure	: Not applicable
Flammable liquids	: Not classified
Flammable solids	: Not applicable
Self-reactive substances and mixtures	: Classification not possible
Pyrophoric liquids	: Classification not possible
Pyrophoric solids	: Not applicable
Self-heating substances and mixtures	: Classification not possible
Substances and mixtures which, in contact with water, emit flammable gases	: Classification not possible
Oxidizing liquids	: Classification not possible
Oxidizing solids	: Not applicable
Organic peroxides	: Classification not possible
Corrosive to metals	: Classification not possible

Health hazards:

Acute toxicity - oral	: Not classified
Acute toxicity - dermal	: Not classified
Acute toxicity-inhalation/gases	: Not applicable
Acute toxicity-inhalation/vapour	: Not classified
Acute toxicity-inhalation/dusts and mists	: Category 5
Skin corrosion / irritation	: Not classified
Serious eye damage / irritation	: Not classified
Respiratory sensitization	: Not classified
Skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Category 1
Reproductive toxicity	: Category 1
Specific target organ systemic toxicity (single exposure)	: Category 1 (Respiratory or gans , Heart , Kidney , Central nervous system)
Specific target organ systemic toxicity (repeated exposure)	: Category 1 (Respiratory or gans , Heart , Central nervous system)
Aspiration toxicity	: Not classified

Environmental hazards:

Hazardous to the aquatic environment (acute toxicity) :Category 3
 Hazardous to the aquatic environment (chronic toxicity) :Not classified

GHS label elements:

Pictogram or symbol:



Signal words: Danger

Hazard statement:

May be harmful if inhaled.
 May cause cancer.
 May damage fertility or the unborn child
 Causes damage to or organs Respiratory or organs, Heart, Kidney, Central nervous system.
 Causes damage to or organs Respiratory or organs, Heart, Central nervous system through prolonged or repeated exposure.
 Harmful to aquatic life.

Precautionary statements:

Prevention:

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Use personal protective equipment as required.
 Do not breathe dust/fume/gas/mist/vapours/spray.
 Wash hands thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Avoid release to the environment-if this is not the intended use.

First aid measures:

If exposing it: Contact the doctor.
 Get medical attention/advice if you feel unwell.
 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container to accordance with local/regional/national/international regulation.

3 . COMPOSITION / INFORMATION ON INGREDIENTS

Classification of the substance or mixture: A mixture.

Chemical or generic name: No information

Chemical characteristic (chemical formulas): No information

Poisonous and Deleterious Substances Control Act: No correspond

Component name:

Ingredient name	CAS no	Content (%)	Industrial Safety and Health Act	Poisonous and Deleterious Substances Control Act	Pollutant Release and Transfer Register Law
ethylene glycol	107-21-1	1.0 ~ 10.0		-	
Mineral oil	72623-86-0	0.1 ~ 1		-	

4 . FIRST AID MEASURES

Inhalation:

If inhaled vapour or gases and felt unwell, remove to fresh air and keep at rest in a position comfortable for breathing.

And call a doctor /physician if feels unwell.

If inhaled vapour or gases in large quantities, remove to fresh air and rest with keeping warm. And if breathing gets irregular or stops, perform artificial respiration. And do not let swallow vomit.

Consult a doctor/ physician immediately.

Skin contact:

Wipe off clinging substance with clean cloth quickly.

Wash off thoroughly with plenty of water and soap. Do not use solvent or paint thinner.

If any change of appearance is seen, or pain persists and feels unwell, consult a doctor/physician.

Eye contact:

Wash off with plenty of clean water immediately for 15 minutes or more. And remove contact lens ,if presence and easy to do.

And completely wash it including the underside of eyelid.

Consult a physician as soon as possible.

Ingestion:

If swallowed accidentally, rest and consult a doctor/physician immediately.

Do not let swallow vomit.

Avoid forcing to vomit without physician ' s instraction.

The protection of the person taking first aid mesure.:

Wear proper protectors (safety goggles, respirator, gloves,etc.)

Ventilate

5 . FIRE-FIGHTING MEASURES

Extinguishing compositions:All extinguishant.

Special fire extinguishing method(protection of fire-fighting person):

Perform fire fighting in cope with protecting to fire neighbor.

6 . ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear proper protectors (safety goggles, respirator, gloves, apron,etc.)

Declare off-limits of the outskirts and do not bring it close anyone other than the person concerned and prevent a second disaster.

Enviromental precautions:

Take cautions not to cause influence on enviroment by discharge to river.

Methods and materials for containment and cleaning up:

Dispose of waste or clinging matter according to related regulation.

Recollect leakage in the container can be sealed and keep in safety place.

7 . HANDLING AND STORAGE

Handling:

Handling technical measures:

Handle in good ventilated area.

Close container tightly with closer after use.

Wear proper protectors to prevent from contact on skin, mucous membrane, wearing clothes and eyes.

Wash hands and face well after handling, and avoid to bring polluted protectors in any place where person stays.

Storage:

Strage, technical measures:

Avoid a direct sunlight.

Keep in good ventilated place.

8 . EXPOSURE CONTROLS / PERSONAL PROTECTION

Taking measures for equipments:

In door application, use either not to expose the operator directly, such as using automatic painting machinees, or that keeps the operator from expsure, such as loacal exhaust ventilation equipment.

Management density / permission density:

Chemical substance name

ACGIH_TLV-C ppm

ACGIH_TLV-C mg/m3

Skin

ethylene glycol

100

Protective equipment:

Respiratory protective equipment:

In working,wear proper protection mask.

Hand protective equipment:

Wear the glove that organic solvents or chemicals can not permeate through.

Eyes protective equipment:

Wear protective eyeglasses or goggles.

Skin and body protective equipment:

Wear suitable clothing that should be impervious to chemicals and to avoid direct contact of skin in handling.

Other information:

Wear electricity shoes on electrostatic painting.

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Physical state:Liquid

Colour:Yellow system

Odour:No information

pH:9.5

Melting point/freezing point:No information

Initial boiling point and boiling range:100[]

Flash point:

Auto-ignition temperature(ignition point):No information

Flammability (solid, gas):No information

Upper/lower flammability or explosive limits:0[vol %] / 0[vol %]

Vapor pressure:No information

Vapour density:No information

Evaporation rate:No information

Specific gravity (relative density):1.21

Solubility:

Solubility in water:No information

Dissolubility in water:No information

Solubility in solvent:No information

Dissolubility in solvent:No information

Partition coefficient:n-octanol/water:No pertinence.

Decomposition temperature:No information

1 0 . STABILITY AND REACTIVITY

Conditions to avoid:

Avoid high temperature.

Avoid an impact./ Avoid a vibration.

Hazardous decomposition products:

Hazardous gases such as low molecular weight monomers are emitted.

Hazardous gases such as carbon monoxide are emitted.

1 1 . TOXICOLOGICAL INFORMATION

Acute toxicity:

ethylene glycol

LD50(oral) 4000mg/kg(4h)

LD50(dermal) 10600mg/kg(4h)

Mineral oil

LD50(oral) rat > 5000mg/kg

LD50(dermal) rat > 5000mg/kg

Skin corrosion/irritation:

ethylene glycol Category 3

Mineral oil Category 3

Serious eye damage /irritation:

ethylene glycol Category 2B

Mineral oil Category 2B

Mutagenicity (germ cell mutagenicity):

Mineral oil Category 2

Carcinogenicity:

Mineral oil Category 1A

Reproductive toxicity:

ethylene glycol Category 1B

Specific target organ / systemic toxicity - single exposure:

ethylene glycol Category 1

(Respiratory or gans , Heart , Kidney , Central nervous system)

Mineral oil Category 2

(Lungs)

Specific target organ / systemic toxicity - repeated exposure:

ethylene glycol Category 1

(Respiratory or gans , Heart , Central nervous system)

Mineral oil Category 1

(Lungs , Skin)

Aspiration hazard:
Mineral oil Category 1

1 2 . ECOLOGICAL INFORMATION

Take care for spills or waste in handling because of its environmental impact. Especially take care for product or rinsing water not to flow into ground, river and drain directly.

1 3 . DISPOSAL CONSIDERATIONS

Residual waste:

Let authorized industrial waste disposing agent to dispose of abolished paint, containers and others under agreement.

Dispose of abolished paint, materials and waste from incineration in accordance with regulation or laws of "Specified Hazardous Industrial Wastes" of Special Controlled Industrial Waste.

Must not dispose of waste water from washing container, machinery and etc. into the ground or drain without treatment.

Dispose of waste from waste water treatment, incineration and etc. in accordance with regulation or laws relating to disposal and cleaning of waste, or let special disposing agent to dispose.

Polluted container and packing:

Let authorized industrial waste disposing agent to dispose of them under agreement.

Dispose of used container after removing contents completely.

1 4 . TRANSPORT INFORMATION

After confirming the state of container had no leakage, and load to prevent collapsing, fall and damage.

Obey the description of "Handling and Storage"

Land transportation:

If falling under "Fire Service Act", "Industrial Safety and Health Act" or "Poisonous and Deleterious Substances Control Act", obey the transport method regulated in each law.

Marine transportation:

Obey the provisions of "Ship Safety Act"

Air transportation:

Obey the provisions of "Civil Aeronautics Act"

1 5 . REGULATORY INFORMATION

Industrial Safety and Health Act:

Article 57-2, notifiable substances

Waste Management and Public Cleansing Act:

1 6 . OTHER INFORMATION

Literatures:

"Raw Materials Database" edited by Japan Paint Manufacturers Association

"Materials Safety Data Sheet Guide (Mixture)" edited by Japan Paint Manufacturers Association

"Solvent Pocket Book" Ohmsha, Ltd.

The Handbook for Precautions and First Aids to Dangerous Goods.

International Chemical Safety Cards.

Other information:

This SDS is necessary to handle our manufacture property and gathered up the matter which must be paid attention briefly for normal handling.

However the content noted above is prepared based on information or data available at the present, the evaluation of hazardousness and harmfulness is not adequate necessary, so be careful in handling.

This SDS may be revised without notice by revising law or new knowledge.

This SDS is based on the standard of Japan Paint Manufacturers Association with Laws of Japan but not from local government, accord to relevant local laws as required when handling.