Date of first issue 1997/01/10 Date of revised 2018/06/29

# SAFETY DATA SHEET

## 1 . IDENTIFICATION

Name of chemical substances: WATER-BASED AQUEOUS MULTIPURPOSE PAINT GREEN

Kinds of product: Acrylic resins emulsion paint

Company name: SUNDAY PAINT Co., Ltd

Address: 6-1-124 Nishikujo, Konohana-ku, Osaka 554-0012 Japan

Section in charge: Mayor of customer service

Phone number: +81-6-6466-6700 FAX number: +81-6-6466-2751 Reference number: 300397

Use:For general

## 2 . HAZARDS IDENTIFICATION

GHS classification:

Physicochemical Hazards:

Explosives :Classification not possible

Flammable gases :Not applicable
Flammable aerosols :Not applicable
Oxidizing gases :Not applicable
Gases under pressure :Not applicable
Flammable liquids :Not classified
Flammable solids :Not applicable

Self-reactive substances and mixtures :Classification not possible Pyrophoric liquids :Classification not possible

Pyrophoric solids :Not applicable

Self-heating substances and mixtures :Classification not possible

Substances and mixtures which, in contact with water, emit flam

mable gases :Classification not possible Oxidizing liquids :Classification not possible

Oxidizing solids :Not applicable

Organic peroxides :Classification not possible Corrosive to metals :Classification not possible

Health hazards:

Acute toxicity - oral :Not classified
Acute toxicity - dermal :Category 5
Acute toxicity-inhalation/gases :Not applicable
Acute toxicity-inhalation/vapour :Not classified

Acute toxicity-inhalation/dusts

and mists :Category 5
Skin corrosion / irritation :Not classified

Serious eye damage /irritation :Not classified Respiratory sensitization :Not classified Skin sensitization :Not classified Germ cell mutagenicity :Not classified Carcinogenicity :Category 1 :Category 1

Specific target organ systemic toxicity (single exposure) :Category 1

(Respiratory or gans, Heart, Kidney, Central nervous s

ystem)

Specific target organ systemic toxicity (repeated exposure)

toxicity (repeated exposure) :Category 1

(Respiratory or gans, Heart, Central nervous system)

:Not classified

Aspiration toxicity Environmental hazards:

Hazardous to the aquatic

environment (acute toxicity)

:Category 3

Hazardous to the aquatic

environment (chronic toxicity) :Not classified

GHS label elements: Pictogram or symbol:



Signal words:Danger Hazard statement:

May be harmful in contact with skin.

May be harmful if inhaled.

May cause cancer.

May damage fertility or the unborn child

Causes damage to or gans Respiratory or gans, Heart, Kidney, Central nervous system.

Causes damage to or gansRespiratory or gans, Heart, Central nervous systemthrough

prolonged or repeated exposure.

Harmful to aquatic life.

# Precautionary statements:

### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid release to the environment-if this is not the intended use.

#### First aid measures:

If exposing it: Contact the doctor.

Get medical attention/advice if you feel unwell.

Call a POISON CENTER/doctor/physician if you feel unwell.

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

## Storage:

Store locked up.

### Disposal:

Dispose of contents/container to accordance with local/regional/national/international regulation.

# 3 . COMPOSITION / INFORMATION ON INGREDIENTS

Classification of the substance or mixture: A mixture.

Chemical or generic name: No information

Chemical characteristic (chemical formulas): No information

Poisonous and Deleterious Substances Control Act:No correspond

Component name:

| Ingredient name     | CAS no     | Content (%) | Industrial Safety<br>and Health Act | Poisonous and Dele<br>terious Substances<br>Control Act |  |
|---------------------|------------|-------------|-------------------------------------|---|--|
| ethylene glycol     | 107-21-1   | 1.0~10.0    |                                     | -   |  |
| C.I.Pigment Green 7 | 1328-53-6  | 0.1~1       |                                     | -   |  |
| silica              | 7631-86-9  | 0.1~1       |                                     | -   |  |
| Mineral oil         | 72623-86-0 | 0.1~1       |                                     | -   |  |
| titanium dioxide    | 13463-67-7 | 0.1~1       |                                     | -   |  |
| titaliium dioxide   | 13403-07-7 | 0.1 - 1     |                                     | -   |  |

# 4 . FIRST AID MEASURES

## Inhalation:

If inhaled vapour or gases and felt unwell, remove to fresh air and keep at rest in a position comfortable for breathing.

And call a doctor /physician if feels unwell.

If inhaled vapour or gases in large quantities, remove to fresh air and rest with keeping war m. And if breathing gets irregular or stops, perform article respiration. And do not let swa llow vormit.

Consult a doctor/ physician immediately.

### Skin contact:

Wipe off clinging substace with clean cloth quickly.

Wash off thoroughly with plenty of water and soap. Do not use solvent or paint thinner.

If any change of appearance is seen, or pain persists and feels unwell,

cosult a doctor/physician.

Take off all contaminated clothing. immediately.

## Eye contact:

Wash off with plenty of clean water immediately for 15 minutes or more. And remove contact lens , if presence and easy to do.

And completely wash it inclouding the underside of eyelid.

Consult a physician as soon as possible.

### Ingestion:

If swallowed accidentally, rest and consult a doctor/physician immediately.

Do not let swallow vomit.

Avoid forcing to vomit without physician's instraction.

The protection of the person taking first aid mesure.:

Wear proper protectors ( safety goggles, respirator, gloves, etc.)

Ventilate

#### 5 . FIRE-FIGHTING MEASURES

Extinguishing compositions: All extinguishant.

Special fire extinguishing method(protection of fire-fighting person):

Perform fire fighting in cope with protecting to fire neighbor.

# 6 . ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear proper protectors (safety goggles, respirator, gloves, apron, etc.)

Declare off-limits of the outskirts and do not bring it close anyone other than the person concerned and prevent a second disaster.

Environmental precautions:

Take causions not to cause influence on environment by discharge to river.

Methods and materials for containment and cleaning up:

Dispose of waste or clinging matter according to related regulation.

Recollect leakage in the container can be sealed and keep in safety place.

## 7 . HANDLING AND STORAGE

## Handling:

Handling technical measures:

Handle in good ventilated area.

Close container tightly with closer after use.

Wear proper protectors to prevent from contact on skin, mucous membrane, wearing clothes an deves.

Wash hands and face well after handling, and avoid to bring polluted protectors in any place where person stays.

### Storage:

Strage, technical measures:

Avoid a direct sunlight.

Keep in good ventilated place.

### 8 . EXPOSURE CONTROLS / PERSONAL PROTECTION

Taking measures for equipments:

In door application, use either not to expose the operator directly, such as using automatic painting machinees, or that keeps the operator from expsure, such as loacal exhaust ventilation equipment.

Management density / permission density:

Chemical substance name ACGIH\_TLV-C ppm ACGIH\_TLV-C mg/m3 Skin

ethylene glycol 100

Chemical substance name ACGIH\_TWA ppm ACGIH\_TWA mg/m3 Skin titanium dioxide 10

Chemical substance name IARC titanium dioxide 3

Carcinogenicity:

```
Protective equipment:
     Respiratory protective equipment:
           In working, wear proper protection mask.
     Hand protective equipment:
          Wear the glove that organic solvents or chemicals can not permeate through.
     Eyes protective equipment:
          Wear protective eyeglasses or goggles.
     Skin and body protective equipment:
          Wear suitable clothing that should be impervious to chemicals and to avoid direct contact
          of skin in handling.
   Other information:
        Wear electricity shoes on electrostatic painting.
9 . PHYSICAL AND CHEMICAL PROPERTIES
   Appearance:
     Physical state:Liquid
     Colour: Green system
   Odour: No information
   pH:9.5
   Melting point/freezing point:No information
   Initial boiling point and boiling range:100[ ]
   Flash point:
   Auto-ignition temperature(ignition point):No information
   Flammability (solid, gas):No information
   Upper/lower flammability or exprosive limits:0[vol %] / 0[vol %]
   Vapor pressure: No information
   Vapour density: No information
   Evaporation rate: No information
   Specific gravity (relative density):1.21
   Solubility:
     Solubility in water: No information
     Dissolubility in water: No information
     Solubility in solvent: No information
     Dissolubility in solvent: No information
   Partition coefficient:n-octanol/water:No pertinence.
   Decomposition temperature: No information
1 0 . STABILITY AND REACTIVITY
   Conditions to avoid:
        Avoid high temperature.
        Avoid an impact. / Avoid a vibration.
   Hazardous decomposition products:
        Hazardous gases such as low molecular weight monomers are emitted.
        Hazardous gases such as carbon monoxide are emitted.
1 1 . TOXICOLOGICAL INFORMATION
   Acute toxicity:
   ethylene glycol
                                                            4000mg/kg(4h)
            LD50(oral)
            LD50(dermal)
                                                            10600mg/kg(4h)
   Mineral oil
            LD50(oral)
                                                            > 5000mg/kg
                                        rat
            LD50(dermal)
                                                            > 5000 \text{mg/kg}
                                        rat
   Skin corrosion/irritation:
             ethylene glycol Category 3
             Mineral oil Category 3
   Serious eye damage /irritation:
             ethylene glycol Category 2B
             Mineral oil Category 2B
             titanium dioxide Category 2B
   Mutagenicity (germ cell mutagenicity):
             Mineral oil Category 2
```

Mineral oil Category 1A

Reproductive toxicity:

ethylene glycol Category 1B

Specific target organ / systemic toxicity - single exposure:

ethylene glycol Category 1

(Respiratory or gans, Heart, Kidney, Central nervous system)

Mineral oil Category 2

(Lungs)

titanium dioxide Category 3

(Respiratory tract irritation)

Specific target organ / systemic toxicity - repeated exposure:

ethylene glycol Category 1

(Respiratory or gans , Heart , Central nervous system)

Mineral oil Category 1

(Lungs, Skin)

Aspiration hazard:

Mineral oil Category 1

# 1 2 . ECOLOGICAL INFORMATION

Take care for spills or waste in handling because of its environmental impact. Especially take care for product or rinsing water not to flow into ground, river and drain directly.

Hazardous to the aquatic environment - Chronic hazard:

titanium dioxide Category 4

## 1 3 . DISPOSAL CONSIDERATIONS

Residual waste:

Let authorized industrial waste disposing agent to dispose of abolished paint, containers and others under agreement.

Dispose of abolished paint, materials and waste from incineration in accordance with regulation or laws of "Specified Hazardous Industrial Wastes" of Special Controlled Industrial Waste.

Must not dispose of waste water from washing container, machinery and etc. into the ground or drain without treatment.

Dispose of waste from waste water treatment, incineration and etc. in accordance with regulation or laws relating to disposal and cleaning of waste, or let special disposing agent to dispose.

Polluted container and packing:

Let authorized industrial waste disposing agent to dispose of them under agreement.

Dispose of used container after removing contents completely.

# 1 4 . TRANSPORT INFORMATION

After confirming the state of container had no leakage, and load to prevent collapsing, fall and damage.

Obey the discription of "Handling and Strage"

Land transportation:

If falling under "Fire Service Act", "Industrial Safety and Health Act" or

"Poisonous and Deleterious Substances Control Act" , obey the transport

method regulated in each law.

Marine transportation:

Obey the provisions of "Ship Safety Act"

Air transportation:

Obey the provisions of "Civil Aeronautics Act"

# 1 5 . REGULATORY INFORMATION

Industrial Safety and Health Act:

Article 57-2, notifiable substances

Waste Management and Public Cleansing Act:

# 1 6 . OTHER INFORMATION

## Literatures:

"Raw Materials Database" edited by Japan Paint Manufacturers Association

"Materials Safety Data Sheet Guide (Mixture)" edited by Japan Paint Manufacturers Association

"Solvent Pocket Book" Ohmsha, Ltd.

The Handbook for Precautions and First Aids to Dangerous Goods.

International Chemical Safety Cards.

# Other information:

This SDS is necessary to handle our manufacture property and gathered up the matter which must be paid attention briefly for normal handling.

However the content noted above is prepared based on information or data available at yhe present, the evaluation of hazardousness and harmfulness is not adequate necessary, so be careful in handling.

This SDS may be revised without notice by revising law or new knowledge.

This SDS is based on the standard of Japan Paint Manufacturers Association with Laws of Japan but not from local government, accord to relevant local laws as required when handling.