

Date of first issue 1998/02/16

Date of revised 2021/07/12

SAFETY DATA SHEET

1 . IDENTIFICATION

Name of chemical substances: SUPER OIL-BASED PAINT FOR IRON AND HOUSING IVORY
 Kinds of product: Acryl modified alkyd resin coating
 Manufacturer name: SUNDAY PAINT Co.,Ltd
 Address: 6F SR Building NAGAHORI,1-18-11, MINAMISEMBA, CHUO-KU, OSAKA 542-0081 Japan
 Section in charge: Mayor of customer service
 Phone number: +81-6-6266-3150
 FAX number: +81-6-6266-3146
 Emergency telephone number: +81-6-6266-3150
 Reference number: 164926
 Use: For general

2 . HAZARDS IDENTIFICATION

GHS classification:

Physicochemical Hazards:

Explosives	:Classification not possible
Flammable gases	:Not applicable
Flammable aerosols	:Not applicable
Oxidizing gases	:Not applicable
Gases under pressure	:Not applicable
Flammable liquids	:Category 3
Flammable solids	:Not applicable
Self-reactive substances and mixtures	:Classification not possible
Pyrophoric liquids	:Classification not possible
Pyrophoric solids	:Not applicable
Self-heating substances and mixtures	:Classification not possible
Substances and mixtures which, in contact with water, emit flammable gases	:Classification not possible
Oxidizing liquids	:Classification not possible
Oxidizing solids	:Not applicable
Organic peroxides	:Classification not possible
Corrosive to metals	:Classification not possible

Health hazards:

Acute toxicity - oral	:Not classified
Acute toxicity - dermal	:Not classified
Acute toxicity-inhalation/gases	:Not applicable
Acute toxicity-inhalation/vapour	:Not classified
Acute toxicity-inhalation/dusts and mists	:Not classified
Skin corrosion / irritation	:Category 2
Serious eye damage /irritation	:Category 2
Respiratory sensitization	:Not classified
Skin sensitization	:Category 1
Germ cell mutagenicity	:Not classified
Carcinogenicity	:Category 2
Reproductive toxicity	:Category 1
Specific target organ systemic toxicity (single exposure)	:Category 1 (Liver , respiratory organs , kidney , Central nervous system)
	:Category 3 (Respiratory tract irritation , Narcotic effects)
Specific target organ systemic toxicity (repeated exposure)	:Category 1

(respiratory organs , Nervous system)
:Category 2

(Liver , Spermary)
:Not classified

Aspiration toxicity

Environmental hazards:

Hazardous to the aquatic
environment (acute toxicity) :Category 1

Hazardous to the aquatic
environment (chronic toxicity) :Category 1

GHS label elements:

Pictogram or symbol:



Signal words: Danger

Hazard statement:

Flammable liquid and vapour.

May cause organic solvent poisoning.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child

Causes damage to organs Liver , respiratory organs , kidney , Central nervous system.

May cause respiratory irritation.

May cause drowsiness and dizziness.

Causes damage to organs respiratory organs , Nervous system through
prolonged or repeated exposure.

May cause damage to organs Liver , Spermary through
prolonged or repeated exposure.

Fatal toxic to aquatic life.

Fatal toxic to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

Keep away from heat/sparks/open flames/hotsurfaces. - No smoking.

Ground/bond container and receiving equipment - if the explosive is electrostatically sensitive.

Use explosion-proof electrical/ventilating/lighting Equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protection gloves, protection glasses, protection side, protection clothes.

Wash thoroughly after handling.

Wear protective gloves as specified by the manufacturer/supplier or the competent authority.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment-if this is not the intended use.

Contaminated work clothing should not be allowed out of the workplace.

Keep container tightly closed.

First aid measures:

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire, use All extinguishant..

IF ON SKIN: Gently wash with plenty of soap and water.

If skin irritation occurs, seek medical advice/attention.

Take off contaminated clothing and wash before reuse.

If exposing it: Contact the doctor.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER/doctor/physician if you feel unwell.
 Get medical attention/advice if you feel unwell.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists, get medical advice/attention.
 Collect spillage.
 If skin irritation occurs, get medical advice/attention.
 Wash contaminated clothing before reuse.

Storage:

Store in cool/well-ventilated place.
 Store locked up.
 Store container tightly closed in well-ventilated place - if product is as volatile as to generate hazardous atmosphere.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulation.

3 . COMPOSITION / INFORMATION ON INGREDIENTS

Classification of the substance or mixture:A mixture.

Chemical or generic name:No information

Chemical characteristic (chemical formulas):No information

Poisonous and Deleterious Substances Control Act:No correspond

Component name:

Ingredient name	CAS no	Content (%)	Industrial Safety and Health Act	Poisonous and Deleterious Substances Control Act	Pollutant Release and Transfer Register Law
mineral spirit	8052-41-3	30.0 ~ 40.0		-	
titanium dioxide	13463-67-7	20.0 ~ 30.0		-	
xylene mixed isomers pure	1330-20-7	2.2		-	PRTR CLASS-1-80
ethylbenzene	100-41-4	1.1		-	PRTR CLASS-1-53
n-Butanol	71-36-3	0.1 ~ 1		-	
zinc oxide	1314-13-2	0.1 ~ 1		-	

4 . FIRST AID MEASURES**Inhalation:**

If inhaled vapour or gases and felt unwell, remove to fresh air and keep at rest in a position comfortable for breathing.

And call a doctor /physician if feels unwell.

Skin contact:

Wipe off clinging substance with clean cloth quickly.

Wash off thoroughly with plenty of water and soap. Do not use solvent or paint thinner.

If any change of appearance is seen, or pain persists and feels unwell, consult a doctor/physician.

Take off immediately all contaminated clothing.

Eye contact:

Wash off with plenty of clean water immediately for 15 minutes or more. And remove contact lens ,if presence and easy to do.

And completely wash it including the underside of eyelid.

Consult a physician as soon as possible.

Call a POISON CENTER or doctor/physician immediately.

Ingestion:

If swallowed accidentally, rest and consult a doctor/physician immediately.

Do not let swallow vomit.

Avoid forcing to vomit without physician ' s instruction.

The protection of the person taking first aid measure.:

Wear proper protectors (safety goggles, respirator, gloves,etc.)

Ventilate

5 . FIRE-FIGHTING MEASURES

Extinguishing compositions:All extinguishant.

Special fire extinguishing method(protection of fire-fighting person):

Wear proper protectors (heat-resistant clothes,etc.)

Remove flammable matters immediately.

Use designated extinguishant.
 If sealed container is exposed to high temperature, water to cool.
 Fire-fight from windward.
 Perform fire fighting in cope with protecting to fire neighbor.

6 . ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear proper protectors (safety goggles, respirator, gloves, apron,etc.)
 Declare off-limits of the outskirts and do not bring it close anyone other than the person concerned and prevent a second disaster.
 Remove ignition source, heat source and flammable matters immediately.
 Prepare proper extinguisher for accidental fire.

Environmental precautions:

Take cautions not to cause influence on environment by discharge to river.

Methods and materials for containment and cleaning up:

Dispose of waste or clinging matter according to related regulation.
 Recollect leakage in the container can be sealed and keep in safety place.
 Recollect with tool of non-spark material.
 Recollect with drysand,soil, or other non-flammable matter. If in large quantity, prevent from flowing out by banking.

7 . HANDLING AND STORAGE

Handling:

Handling technical measures:

Handle in good ventilated area.
 Close container tightly with closer after use.
 Take away from open flame, spark,heat-source
 Wear proper protectors to prevent from contact on skin, mucous membrane, wearing clothes and eyes.
 Wash hands and face well after handling, and avoid to bring polluted protectors in any place where person stays.
 In closed place, ensure good local exhaust ventilation and wear proper protectors.
 The person who had allergic symptom must not handle it.

Handling instructions:

A material product that contains Class 2 Organic Solvents on exceeding 5% is obligated to be stored in a closed equipment or in local exhaust ventilation equipment.

Storage:

Storage, technical measures:

Avoid a direct sunlight.
 Keep in good ventilated place.
 Keep away from open flame and heat source.

8 . EXPOSURE CONTROLS / PERSONAL PROTECTION

Taking measures for equipment:

Use explosion proof type equipment.
 Install ventilation equipment to prevent concentrating of vapour.
 Ground equipment for transferring, pumping and stirring of fluid.
 Provide equipment devised so that heat or ignition source can not be placed in the neighborhood of handling place.
 Consider so that the operator can not touch or expose to corrosive substance directly.
 In door application, use either not to expose the operator directly, such as using automatic painting machines, or that keeps the operator from exposure, such as local exhaust ventilation equipment.

Management density / permission density:

Chemical substance name	Exposure limits ppm	Exposure limits mg /m3	Skin
xylene mixed isomers pure	50		
ethylbenzene	20		
n-Butanol	25		
Chemical substance name	Japan Society for Occupational Health h (JSOH) - ppm	Japan Society for Occupational Health h (JSOH) - mg/m3	Skin

xylene mixed isomers pure	50		
ethylbenzene	50	217	
Chemical substance name	ACGIH_TWA ppm	ACGIH_TWA mg/m3	Skin
mineral spirit	100		
titanium dioxide		10	
xylene mixed isomers pure	100	434	
ethylbenzene	20		
n-Butanol	20		
zinc oxide		2	
Chemical substance name	IARC		
titanium dioxide	2B		
xylene mixed isomers pure	3		
ethylbenzene	2B		

Protective equipment:**Respiratory protective equipment:**

Wear a gas mask for poisonous gases.

Wear a mask with supplying air in closed place.

Hand protective equipment:

Wear the glove that organic solvents or chemicals can not permeate through.

Eyes protective equipment:

Wear protective eyeglasses or goggles.

Skin and body protective equipment:

Wear suitable clothing that should be impervious to chemicals and to avoid direct contact of skin in handling.

Other information:

Wear electricity shoes on electrostatic painting.

9 . PHYSICAL AND CHEMICAL PROPERTIES**Appearance:**

Physical state:Liquid

Colour:No information

Odour:No information

pH:No information

Melting point/freezing point:No information

Initial boiling point and boiling range:160[] ~ 191[]

Flash point:41[]

Auto-ignition temperature(ignition point):255[]

Flammability (solid, gas):No information

Upper/lower flammability or explosive limits:6[vol %] / 0.7[vol %]

Vapor pressure:8[Pa] (20[])

Vapour density:No information

Evaporation rate:No information

Specific gravity (relative density):1.13

Solubility:

Solubility in water:No information

Dissolubility in water:No information

Solubility in solvent:No information

Dissolubility in solvent:No information

Partition coefficient:n-octanol/water:

xylene mixed isomers pure 3.16

ethylbenzene 3.15

Decomposition temperature:No information

1 0 . STABILITY AND REACTIVITY**Stability(possibility of hazardous reaction) :**

There is no dangerous reaction in the range of room temperature.

Product is considered stable.

Conditions to avoid:

Avoid high temperature.

Hazardous decomposition products:

Hazardous gases such as carbon monoxide may be generated.

1 1 . TOXICOLOGICAL INFORMATION

Acute toxicity:

xylene mixed isomers pure

LD50(oral)	4300mg/kg(4h)
LD50(dermal)	> 4350mg/kg(4h)
LC50(vapour)	6700ppm(4h)

ethylbenzene

LD50(oral)	3500mg/kg(4h)
LD50(dermal)	15400mg/kg(4h)
LC50(vapour)	4000ppm(4h)

n-Butanol

LD50(oral)	1227mg/kg(4h)
LD50(dermal)	3636mg/kg(4h)
LC50(vapour)	> 8000ppm(4h)

zinc oxide

LD50(oral)	mouse	> 5000mg/kg
LC50(dust,mist)	rat	= 5.7m g / l (4h)

Skin corrosion/irritation:

mineral spirit	Category 2
xylene mixed isomers pure	Category 2
ethylbenzene	Category 3
n-Butanol	Category 2

Serious eye damage /irritation:

titanium dioxide	Category 2B
xylene mixed isomers pure	Category 2A
ethylbenzene	Category 2B
n-Butanol	Category 2A

Carcinogenicity:

ethylbenzene	Category 2
--------------	------------

Reproductive toxicity:

xylene mixed isomers pure	Category 1B
zinc oxide	Category 2

Specific target organ / systemic toxicity - single exposure:

mineral spirit	Category 3	(Respiratory tract irritation , Narcotic effects)
titanium dioxide	Category 3	(Respiratory tract irritation)
xylene mixed isomers pure	Category 1	(Liver , respiratory organs , kidney , Central nervous system)
	Category 3	(Narcotic effects)
ethylbenzene	Category 2	(Central nervous system)
	Category 3	(Respiratory tract irritation)
n-Butanol	Category 3	(Respiratory tract irritation , Narcotic effects)
zinc oxide	Category 1	(Systemic toxicity , Lungs)

Specific target organ / systemic toxicity - repeated exposure:

mineral spirit	Category 2	(Liver , Spermary)
xylene mixed isomers pure	Category 1	(respiratory organs , Nervous system)
n-Butanol	Category 1	(Central nervous system , Auditory system)

Aspiration hazard:

mineral spirit	Category 1
xylene mixed isomers pure	Category 2
ethylbenzene	Category 1
n-Butanol	Category 2

1 2 . ECOLOGICAL INFORMATION

Take care for spills or waste in handling because of its environmental impact. Especially take care for product or rinsing water not to flow into ground, river and drain directly.

Hazardous to the aquatic environment - Acute hazard:

mineral spirit Category 1
xylene mixed isomers pure Category 2
ethylbenzene Category 1
zinc oxide Category 1

Hazardous to the aquatic environment - Chronic hazard:

mineral spirit Category 1
titanium dioxide Category 4
xylene mixed isomers pure Category 2
zinc oxide Category 1

1 3 . DISPOSAL CONSIDERATIONS

Residual waste:

Let authorized industrial waste disposing agent to dispose of abolished paint, containers and others under agreement.

Dispose of abolished paint, materials and waste from incineration in accordance with regulation or laws of "Specified Hazardous Industrial Wastes" of Special Controlled Industrial Waste.

Must not dispose of waste water from washing container, machinery and etc. into the ground or drain without treatment.

Dispose of waste from waste water treatment, incineration and etc. in accordance with regulation or laws relating to disposal and cleaning of waste, or let special disposing agent to dispose.

Incinerate abolished paint absorbed to diatomaceous earth by small quantity in the open-type incinerator. Or incinerate them by spraying in the fire box. If it is apprehended that hazardous gases such as dioxins are generated, let authorized industrial waste disposing agent to dispose under agreement.

Let authorized industrial waste disposing agent to dispose of abolished paint and materials under agreement, because there are specified as Special Controlled Industrial waste(waste oil).

Polluted container and packing:

Let authorized industrial waste disposing agent to dispose of them under agreement.

Dispose of used container after removing contents completely.

1 4 . TRANSPORT INFORMATION

After confirming the state of container had no leakage, and load to prevent collapsing, fall and damage.

Obey the description of "Handling and Storage"

UN number:1263

Land transportation:

If falling under "Fire Service Act", "Industrial Safety and Health Act" or "Poisonous and Deleterious Substances Control Act", obey the transport method regulated in each law.

Marine transportation:

Obey the provisions of "Ship Safety Act"

Air transportation:

Obey the provisions of "Civil Aeronautics Act"

Guide number:128

1 5 . REGULATORY INFORMATION

Fire and Disaster Management Act:

Specified Combustible, Flammable liquids .

Industrial Safety and Health Act:

Table 1-4 by Act of Parliament, Flammable material

Article 57-2, notifiable substances

Ordinance on Prevention of Organic Solvent Poisoning, Class 3 Organic Solvents

Waste Management and Public Cleaning Act:

Pollutant Release and Transfer Register Law:

Class 1

1 6 . OTHER INFORMATION

Literatures:

"Raw Materials Database" edited by Japan Paint Manufacturers Association

"Materials Safety Data Sheet Guide (Mixture)" edited by Japan Paint Manufacturers Association

"Solvent Pocket Book" Ohmsha, Ltd.

The Handbook for Precautions and First Aids to Dangerous Goods.

International Chemical Safety Cards.

Other information:

This SDS is necessary to handle our manufacture property and gathered up the matter which must be paid attention briefly for normal handling.

However the content noted above is prepared based on information or data available at the present, the evaluation of hazardousness and harmfulness is not adequate necessary, so be careful in handling.

This SDS may be revised without notice by revising law or new knowledge.

This SDS is based on the standard of Japan Paint Manufacturers Association with Laws of Japan but not from local government, accord to relevant local laws as required when handling.