

# SAFETY DATA SHEET

Reference number : 53300

(Old reference number : 055-0010)

## 1. IDENTIFICATION

Product name : ENAMEL SPRAY EXCEED SKYBLUE  
Kinds of product : Alkyd resin coating (AEROSOL SPRAY PAINT)  
Manufacturer :  
Company name : SUNDAY PAINT Co., Ltd  
Address : 6F SR Building NAGAHORI 1-18-11, MINAMISEMBA, CHUO-KU, OSAKA 542-0081 Japan  
Charge section : Mayor of customer service  
Phone number : +81-6-6266-3150  
Fax number : +81-6-6266-3146  
Emergency telephone number : +81-6-6266-3150  
Product use : For rolling stock  
Date of issue : March 19, 2001  
Date of prepared : August 13, 2019

## 2. HAZARDS IDENTIFICATION

### GHS classification

#### Physicochemical Hazards

Explosives : Not classified  
Flammable gases : Not applicable  
Flammable aerosols : Category 2  
Oxidizing gases : Not applicable  
Gases under pressure : Not applicable  
Flammable liquids : Category 3  
Flammable solids : Not applicable  
Self-reactive substances and mixtures : Classification not possible  
Prophetic liquids : Not classified  
Prophetic solids : Not applicable  
Self-heating substances and mixtures : Not classified  
Substances and mixtures which, in contact with water, emit flammable gases : Not classified  
Oxidizing liquids : Not classified  
Oxidizing solids : Not applicable  
Organic peroxides : Classification not possible  
Corrosive to metals : Classification not possible

#### Health hazards

Acute toxicity - oral : Not classified  
Acute toxicity - dermal : Not classified  
Acute toxicity - inhalation / gas : Not applicable  
Acute toxicity-inhalation/vapour : Not classified  
Acute toxicity-inhalation/dusts and mists : Not classified  
Skin corrosion / irritation : Category 2  
Serious eye damage /irritation : Category 2  
Respiratory sensitization : Not classified  
Skin sensitization : Category 1  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 1  
Specific target organ systemic toxicity (single exposure) : Category 1  
(Liver, Respiratory or gans, Kidney, Central nervous system)  
Category 3  
(Respiratory tract irritation, Narcotic effects)  
Specific target organ systemic toxicity (repeated exposure) : Category 1

(Respiratory or gans, Nervous system)

Category 2

(Liver, Spermary)

Aspiration toxicity

: Not classified

---

### Environmental hazard

---

Hazardous to the aquatic environment (acute toxicity) : Category 1

Hazardous to the aquatic environment chronic hazard : Category 1

---

### GHS label elements

---

#### Pictogram or symbol

---



---

#### Signal word

Danger

---

#### Hazard statement

---

- The combustibility and flammable aerosol.
  - Pressurized container: may burst if heated.
  - Flammable liquid and vapour.
  - May cause organic solvent poisoning.
  - Causes skin irritation.
  - Causee serious eye irritation.
  - May cause an allergic skin reaction.
  - Suspected of causing cancer.
  - May damage fertility or the unborn child.
  - Causes damage to organs Liver, Respiratory or gans, Kidney, Central nervous system.
  - May cause drowsiness and dizziness.
  - Causes damage to organs Respiratory or gans, Nervous system through prolonged or repeated exposure.
  - May causes damage to organs Liver, Spermary through prolonged or repeated exposure.
  - Fatal to aquatic life.
  - Fatal to aquatic life with long lasting effects.
- 

#### Precautionary statements

---

##### Prevention

---

- Keep away from heat/sparks/open flames/hotsurfaces. - No smoking.
  - Ground/bond container and receiving equipment - if the explosive is electrostatically sensitive.
  - Use explosion-proof electrical/ventilating/lighting Equipment.
  - Use only non-sparking tools.
  - Take precautionary measures against static discharge.
  - Wear protection gloves, protection glasses, protection side, protection clothes.
  - Wash thoroughly after handling.
  - Wear protective gloves as specified by the manufacturer/supplier or the competent authority.
  - Obtain special instructions before use.
  - Do not handle until all safety precautions have been read and understood.
  - Use personal protective equipment as required.
  - Do not breathe dust/fume/gas/mist/vapours/spray.
  - Wash hands thoroughly after handling.
  - Do not eat, drink or smoke when using this product.
  - Use only outdoors or in a well-ventilated area.
  - Avoid release to the environment - if this is not the intended use.
  - Contaminated work clothing should not be allowed out of the workplace.
  - Keep container tightly closed.
- 

##### First aid measures

---

- If on skin (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- In case of fire, use Carbon dioxide gas, foam, dry powder.
- IF ON SKIN: Gently wash with plenty of soap and water.
- If skin irritation occurs, seek medical advice/attention.
- Take of contaminated clothing and wash before re-use.
- If exposing it: Contact the doctor.
- IF exposed: Call a POISON CENTER or doctor/physician.

- If inhaled: Remove to fresh air and keep at rest in a position comfortable for breathing.
- Call a poison center/doctor/physician if you feel unwell.
- Get medical attention/advice if you feel unwell.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists, get medical advice/attention.
- Collect spillage.
- If skin irritation occurs, get medical advice/attention.
- Wash contaminated clothing before re-use.

---

#### Storage

---

- Store in cool/well-ventilated place.
- Store locked up.
- Store container tightly closed in well-ventilated place - if product is as volatile as to generate hazardous

---

#### Disposal

---

- Dispose of contents/container to accordance with local/regional/national/international regulation.
- 

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

---

Classification of the substance or mixture	: A mixture.
Chemical or generic name	: No information.
Chemical characteristic (chemical formulas)	: No information.
Poisonous and Deleterious Substances Control Act	: No correspond.
Ingredient	:

---

Ingredient name	CAS no	Content (%)	Industrial Safety and Health Act	Poisonous and Deleterious Substances Control Act	Pollutant Release and Transfer Register Law (PRTR)
mineralsprits	8052-41-3	10.0~20.0	○	—	
xylene mixed isomers pure	1330-20-7	10.8	○	—	CLASS-1- 80
ethylbenzene	100-41-4	6.6	○	—	CLASS-1- 53
titanium dioxide	13463-67-7	1.0~10.0	○	—	
C.I.Pigment Blue 15	147-14-8	1.0~10.0	○	—	
aluminium oxide	1344-28-1	0.1~1.0	○	—	
cobalt bis(8,2-ethylhexanoate)	136-52-7	0.1~1.0	○	—	CLASS-1-132 (Out of object)
dimethyl ether	115-10-6	40.0~50.0	—	—	

---

### 4. FIRST AID MEASURES

---

#### Inhalation

---

- If inhaled vapour or gases and felt unwell, remove to fresh air and keep at rest in a position comfortable for breathing. And call a doctor /physician if feels unwell.

#### Skin contact

---

- Wipe off clinging substance with clean cloth quickly.
- Wash off thoroughly with plenty of water and soap. Do not use solvent or paint thinner.
- If any change of appearance is seen, or pain persists and feels unwell, consult a doctor/physician.
- Take off all contaminated clothing. Immediately.

#### Eye contact

---

- Wash off with plenty of clean water immediately for 15minutes or more. And remove contact lens ,if presence and easy And completely wash it including the underside of eyelid.
- Consult a physician as soon as possible.
- Call a POISON CENTER or doctor/physician immediately.

#### Ingestion

---

- If swallowed accidentally, rest and consult a doctor/physician immediately.
- Do not let swallow vomit.
- Avoid forcing to vomit without physician's instruction.

#### The protection of the person taking first aid measure

---

- Wear proper protectors ( safety goggles, respirator, gloves,etc.)
- Ventilate

### 5. FIRE-FIGHTING MEASURES

---

Extinguishing media : Carbon dioxide gas, foam, dry powder

Must not use extinguishing media : Water (stick water, high pressure water jet)

Special fire extinguishing method(Protection of fire-fighting person)

- Wear proper protectors (heat-resistant clothes, etc.)
- Remove flammable matters immediately.
- Use designated extinguishant.
- If sealed container is exposed to high temperature, water to cool.
- Fire-Fight from windward.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### Personal precautions, protective equipment and emergency procedures

---

- Wear proper protectors (safety goggles, respirator, gloves, apron, etc.)
- Declare off-limits of the outskirts and I do not bring it close anyone other than the person concerned and prevent a second disaster.
- Remove ignition source, heat source and flammable matters immediately.
- Prepare proper extinguisher for accidental fire.

### Environmental precautions

---

- Take cautions not to cause influence on environment by discharge to river.

### Methods and materials for containment and cleaning up

---

- Dispose of waste or clinging matter according to related regulation.
- Recollect leakage in the container can be sealed and keep in safety place.
- Recollect with tool of non-spark material.
- Recollect with dry sand, soil, or other nonflammable matter. If in large quantity, prevent from flowing out by banking.

---

## 7. HANDLING AND STORAGE

---

### Handling

---

#### Handling technical measures

---

- Handle in good ventilated area.
- Close container tightly with closer after use.
- Take away from open flame, spark, heat-source.
- Use a non-spark type hand tool.
- While working, wear antistatic working suits and shoes.
- Wear proper protectors to prevent from contact on skin, mucous membrane, wearing clothes and eyes.
- Wash hands and face well after handling, and avoid to bring polluted protectors in any place where person stays.
- In closed place, ensure good local exhaust ventilation and wear proper protectors.

#### Handling instructions

---

- As a measure against static electricity accident, ground equipment and use electric appliances of explosion proof type.
- A material product that contains Class 2 Organic Solvents on exceeding 5% is obligated to be stored in a closed equipment or in local exhaust ventilation equipment.

### Storage

---

#### Storage, technical measures

---

- Avoid a direct sunlight.
- Keep in good ventilated place.
- Keep away from open flame and heat source.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Taking measures for equipments:

---

- Use explosion proof type equipment.
- Install ventilation equipment to prevent concentrating of vapour.
- Ground equipment for transferring, pumping and stirring of fluid.
- the devices such as the churning.
- Provide equipment devised so that heat or ignition source can not be placed in the neighborhood of handling place.
- In door application, use either not to expose the operator directly, such as using automatic painting machines, or that keeps the operator from exposure, such as local exhaust ventilation equipment.
- In application in closed space such as inside of tank, install equipment that can ventilate completely even its bottom.
- Consider so that the operator can not touch or expose to corrosive substance directly.

### Management density / permission density

---

Chemical substance name	Exposure limits-ppm	Exposure limits-mg/m <sup>3</sup>	skin
xylene mixed isomers pure	50	—	—
ethylbenzene	20	—	—

Chemical substance name	Japan Society for Occupational Health (JSOH) - ppm	Japan Society for Occupational Health (JSOH) -mg/m3	skin
mineralsprits	—	—	—
xylene mixed isomers pure	50	—	—
ethylbenzene	50	217	—

Chemical substance name	ACGIH_TWA - ppm	ACGIH_TWA -mg/m3	skin
mineralsprits	100	—	—
xylene mixed isomers pure	100	434	—
ethylbenzene	20	—	—
titanium dioxide	—	10	—
aluminium oxide	—	10	—

Chemical substance name	IARC
xylene mixed isomers pure	3
ethylbenzene	2B
titanium dioxide	2B
cobalt bis(8,2-ethylhexanoate)	2B

### Tool for protection

#### Respiratory protective equipment

- Wear a gas mask for organic gases.
- Wear a mask with supplying air in closed place.

#### Hand protective equipment

- Wear the glove that organic solvents or chemicals can not permeate through.

#### Eyes protective equipment

- Wear protective eyeglasses or goggles.

#### Skin and body protective equipment

- Wear suitable clothing that should be impervious to chemicals and to avoid direct contact of skin in handling.

#### Other information

- Wear electricity shoes on electrostatic painting.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

	[ Propellant ]	[ Paint ]
Appearance		
Physical state	: Gas	Liquid
Color	: No information.	Skyblue
Odor	: No information.	Solvents Smell
Ph	: No information.	No information.
Melting point/freezing point	: No information.	No information.
Initial boiling point and boiling	: -24.8 °C	130 ~ 230 °C
Flash point	: -41.4 °C	31 °C
Auto-ignition temperature(ignition point)	: 350 °C	288 °C
Flammability (solid, gas)	: No information.	No information.
Upper/lower flammability or explosive limits	: 27.0/3.4 vol %	8 / 0.6 vol %
Vapor pressure(°C)	: 257230 (0)	1400 (Pa( 20 )
Vapor density	: No information.	No information.
Evaporation rate	: No information.	No information.
Specific gravity (relative density)	: 0.67	1.07
Solubility		
Solubility for the water	: No information.	
Dissolubility for the water	: No information.	
Solubility for the solvent	: No information.	
Dissolubility for the solvent	: No information.	
Partition coefficient:n-octanol/water		
xylene mixed isomers pure	: 3.16	
ethylbenzene	: 3.15	
Decomposition temperature	: No information.	

## 10. STABILITY AND REACTIVITY

---

**Conditions to avoid**

---

- Avoid high temperature.
  - Avoid an impact. / Avoid a vibration.
- 

**Hazardous decomposition products**

---

- Hazardous gases such as low molecular weight monomers are emitted.
  - Hazardous gases such as carbon monoxide are emitted.
- 

**Other information on hazardousness**

---

- Inside pressure of a container is 4.5kg/cm<sup>3</sup> (20°C)
  - High-pressure gas , and an inflammability
  - Anesthetic (very weak)
  - As touch the liquefied gas, there is a possibility of inflammation or frostbite.
- 

**11. TOXICOLOGICAL INFORMATION**

---

**Acute toxicity**

---

xylene mixed isomers pure	: LD50(oral)	—	4300mg/kg(4h)
	LD50(dermal)	—	>4350mg/kg(4h)
	LC50(vapour)	—	6700ppm(4h)
	LC50(dust/mist)	—	—
ethylbenzene	: LD50(oral)	—	3500mg/kg (4h)
	LD50(dermal)	—	15400mg/kg (4h)
	LC50(vapour)	—	4000ppm (4h)
	LC50(dust/mist)	—	—
aluminium oxide	: LD50(oral)	rat	>5000mg/kg
	LD50(dermal)	—	—
	LC50(vapour)	—	—
	LC50(dust/mist)	—	—

---

**Skin corrosion/irritation**

---

mineralsprits	: Category 2
xylene mixed isomers pure	: Category 2
ethylbenzene	: Category 3

---

**Serious eye damage /irritation**

---

xylene mixed isomers pure	: Category 2A
ethylbenzene	: Category 2B
titanium dioxide	: Category 2B

---

**Carcinogenicity**

---

ethylbenzene	: Category 2
--------------	--------------

---

**Teratogenicity**

---

xylene mixed isomers pure	: Category 1B
---------------------------	---------------

---

**Specific target organ / systemic toxicity - single exposure**

---

mineralsprits	: Category 3 (Respiratory tract irritation, Narcotic effect)
xylene mixed isomers pure	: Category 1 (Liver, Respiratory organs, Kidney, Central nervous system) Category 3 (Narcotic effects)
ethylbenzene	: Category 2 (Central nervous system) Category 3 (Respiratory tract irritation)
titanium dioxide	: Category 3 (Respiratory tract irritation)

---

**Specific target organ / systemic toxicity - repeated exposure**

---

mineralsprits	: Category 2 (Liver, Spermary)
xylene mixed isomers pure	: Category 1 (Respiratory organs, Nervous system)

---

**Aspiration hazard**

---

mineralsprits	: Category 1
xylene mixed isomers pure	: Category 2
ethylbenzene	: Category 1

---

**12. ECOLOGICAL INFORMATION**

---

- Take care for spills or waste in handling because of its environmental impact. Especially take care for product or rinsing water not to flow into ground, river and drain directly.
- 

**Hazardous to the aquatic environment - Acute hazard**

---

mineralsprits	: Category 1
---------------	--------------

---

xylene mixed isomers pure : Category 2  
ethylbenzene : Category 1

---

### Hazardous to the aquatic environment - Chronic hazard

---

mineralsprits : Category 1  
xylene mixed isomers pure : Category 2  
titanium dioxide : Category 4

---

## 13. DISPOSAL CONSIDERATIONS

---

### Residual waste

---

- Let authorized industrial waste disposing agent to dispose of abolished paint, containers and others under agreement. Dispose of abolished paint, materils and waste from incineration in accordance with regulation or laws of "Specified Hazardous Industrial Wastes" of Special Controlled Industrial Waste.
  - Must not dispose of waste water from washing container, machinery and etc. into the ground or drain without treatment.
  - Dispose of waste from waste water treatment, incineration and etc. in accordance with regulation or laws relating to disposal and cleaning of waste, or let special disposing agent to dispose.
  - Incinerate abolished paint absorbed to diatomaceous earth by small quantity in the open-type incinerator. Or incinerate them by spraying in the fire box. If it is apprehended that hazardous gases such as dioxins are generated, let authorized industrial waste disposing agent to dispose under agreement."
  - Let authorized industrial waste disposing agent to dispose of abolished paint and materials under agreement, because there are specified as Special Controlled Industrial waste (waste oil).
- 

### Pollution container and packing:

---

- Let authorized industrial waste disposing agent to dispose of them under agreement.
  - Dispose of used container after removing contents completely.
- 

## 14. TRANSPORT INFORMATION

---

- After confirming the state of container had no leakage, and load to prevent collapsing, fall and damage.
- Obey the discription of "Handling and Strage"

UN number : 1950

---

### Land transportation

- If falling under "Fire Service Act", "Industrial Safety and Health Act" or "Poisonous and Deleterious Substances Control Act", obey the transport method regulated in each law.
- 

### Marine transportation

- Obey the provisions of "Ship Safety Act"
- 

### Air transport

- Obey the provisions of "Civil Aeronautics Act"

Indicator number : 126

IMQ class : 2.1 (Inflammable gas)

---

## 15. REGULATORY INFORMATION

---

### Fire and Disaster Management Act

- Dangerous Materials Class 4 Group 2 Petroleum, Non-Solution, dangerous grades III.
- 

### Industrial Safety and Health Act

- Table 1-4 by Act of Parliament, Flammable material
  - Article 57-2, notifiable substances
  - Ordinance on Prevention of Organic Solvent Poisoning, Class 2 Organic Solvents
- 

### High pressure gas control law

- Liquefied gas, Flammable gas (except: aerosol)
- 

### Special Management Industrial Waste

- -
- 

### Pollutant Release and Transfer Register

- Class 1
- 

## 16. OTHER INFORMATION

---

### Literatures

---

- "Raw Materials Database" edited by Japan Paint Manufacturers Association
  - Materials Safety Data Sheet Guide (Mixture)" edited by Japan Paint Manufacturers Association
  - "Solvent Pocket Book" Ohmsha, Ltd.
  - The Handbook for Precautions and First Aids to Dangerous Goods.
  - International Chemical Safety Cards.
- 

### Other information

---

- This SDS is necessary to handle our manufacture property and gathered up the matter which must be paid attention briefly for normal handling.
- However the content noted above is prepared based on information or data available at yhe present, the evaluation of hazardousness and harmfulness is not adequate necessary, so be careful in handling.
- This SDS may be revised without notice by revising law or new knowledge.
- This SDS is based on the standard of Japan Paint Manufacturers Association with Laws of Japan but not from local government, accord to relevant local laws as required when handling.