

**Aluminium Paint****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Aluminium Paint
Code-Nr. 150020

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Liquids

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone +49(0)251 / 9322 - 0, Fax +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone +49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Flam. Liq. 3	H226	
Eye Irrit. 2	H319	
STOT SE 3	H335, H336	
Asp. Tox. 1		
Aquatic Chronic 3	H412	

Hazard Statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

! Signal word

Warning

Hazard Statements

H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/eye protection.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P331 Do NOT induce vomiting.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P362 Take off contaminated clothing.
 P370 + P378 In case of fire: Use dry sand to extinguish.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

butan-1-ol, Solvent naphtha (petroleum), light arom. (NOTA P), n-butyl acetate, xylene

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Aluminium Paint****Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Coating paint

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
71-36-3	200-751-6	butan-1-ol	1 < 3	Flam. Liq. 3, H226 / Acute Tox. 4, H302 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Eye Dam. 1, H318 / STOT SE 3, H336
100-41-4	202-849-4	ethylbenzene	1 < 10	Flam. Liq. 2, H225 / Acute Tox. 4, H332 / STOT RE 2, H373 (hearing organs) / Asp. Tox. 1, H304
123-86-4	204-658-1	n-butyl acetate	10 < 20	Flam. Liq. 3, H226 / STOT SE 3, H336
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	20 < 25	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / , EUH066
7429-90-5		aluminium powder (stabilised)	10 < 20	Flam. Sol. 1, H228 / Water-react., H261
1330-20-7	215-535-7	xylene	5 < 10	Flam. Liq. 3, H226 / STOT RE 2, H373 / Asp. Tox. 1, H304 / Acute Tox. 4, H312, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / STOT SE 3, H335

REACH

CAS No	Name	REACH registration number
1330-20-7	xylene	01-2119488216-32-xxxx

! SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

! In case of eye contact

In case of contact with eyes rinsing with plenty of lukewarm water carefully and seek for medical treatment.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.



4.2. Most important symptoms and effects, both acute and delayed

! Physician's information / possible symptoms

vomiting

Respiratory complaints

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Dry powder

Dry sand

Unsuitable extinguishing media

water

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

! Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

! Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

! For non-emergency personnel

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Protect from water.

Ventilate area concerned

Take up with absorbent material (e.g. sand, sawdust).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store with acids.

Keep at distance to ignition device, water and alkalis.

Do not store together with oxidizing agents.

! Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Protect from wetness.

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
7429-90-5	Aluminium metal: inhalable dust	8 hours	10		EH40/2005
7429-90-5	Aluminium metal: respirable dust	8 hours	4		EH40/2005



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 12.04.2017
revision 22.08.2016 (GB) Version 9.0

Aluminium Paint

Ingredients with occupational exposure limits to be monitored (continued)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
71-36-3	butan-1-ol	8 hours Short-term	154	50	EH40/2005
100-41-4	Ethylbenzene	8 hours Short-term	441 552	100 125	EH40/2005
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours Short-term	220 441	50 100	EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
100-41-4	ethylbenzene	8 hours Short-term	442 884	100 200	skin

**DNEL-/PNEC-values
DNEL worker**

CAS No	Substance name	Value	Code	Remark
123-86-4	n-butyl acetate	480 mg/m ³	DNEL long-term inhalative (systemic)	
		11 mg/kg	DNEL long-term dermal (systemic)	
		2 mg/kg	DNEL short-term oral (acute)	
		11 mg/kg	DNEL acute dermal, short-term (systemic)	
		600 mg/m ³	DNEL acute inhalative (local)	
		960 mg/m ³	DNEL acute inhalative (systemic)	
		300 mg/m ³	DNEL long-term inhalative (local)	
1330-20-7	xylene	289 mg/m ³	DNEL acute inhalative (systemic)	
		289 mg/m ³	DNEL acute inhalative (local)	
		289 mg/m ³	DNEL acute inhalative (local)	
		77 mg/m ³	DNEL long-term inhalative (systemic)	
		180 mg/kg	DNEL long-term dermal (systemic)	
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	25 mg/kg	DNEL long-term dermal (systemic)	
		150 mg/m ³	DNEL long-term inhalative (systemic)	
71-36-3	butan-1-ol	55 mg/m ³	DNEL long-term inhalative (local)	
		3,125 mg/kg bw/day	DNEL long-term oral (repeated)	
		310 mg/m ³	DNEL long-term inhalative (local)	

DNEL Consumer

CAS No	Substance name	Value	Code	Remark
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	11 mg/kg	DNEL long-term oral (repeated)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 12.04.2017

revision 22.08.2016 (GB) Version 9.0

Aluminium Paint

PNEC

CAS No	Substance name	Value	Code	Remark
123-86-4	n-butyl acetate	0,018 mg/l	PNEC aquatic, marine water	
		0,18 mg/l	PNEC aquatic, freshwater	
		0,981 mg/kg	PNEC sediment, freshwater	
1330-20-7	xylene	12,46 mg/kg	PNEC sediment, marine water	
		2,31 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, freshwater	
		12,46 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, marine water	
71-36-3	butan-1-ol	0,0082 mg/l	PNEC aquatic, marine water	
		0,082 mg/l	PNEC aquatic, freshwater	
		0,178 mg/kg	PNEC sediment, freshwater	
		0,0178 mg/kg	PNEC sediment, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

liquid

Colour

silver-coloured

Odour

solvent-like

Odour threshold

**Aluminium Paint**

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	126 °C				
melting point	not determined				
Flash point	27 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	0,6 Vol-%				
Upper explosion limit	10,4 Vol-%				
Vapour pressure	not applicable				
Relative density	1 g/cm ³				
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	> 21 mm ² /s	40 °C			

Oxidising properties

No information available.

Explosive properties

No information available.

9.2. Other information

No information available.

! SECTION 10: Stability and reactivity
10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

Reactions with strong oxidising agents.

Formation of explosive gas/air mixtures.

Reactions with water.

Reactions with alkalies.

10.4. Conditions to avoid

After contact with water:

hydrogen

Keep away from heat.

10.5. Incompatible materials
! Substances to avoid

Alkali (lye)

Acid, concentrated

Oxidising agent, strong

Water

10.6. Hazardous decomposition products

Gases/vapours, toxic

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information
11.1. Information on toxicological effects
Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		CAS: 64742-82-1
LD50 acute dermal	> 2000 mg/kg			ATE
LC50 acute inhalation	> 20 mg/l (4 h)			ATE
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	irritant			
Skin sensitization	non-sensitizing			

**Aluminium Paint****Subacute Toxicity - Carcinogenicity**

Value	Species	Method	Validation
Mutagenicity			No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity			No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity			No indications of carcinogenic effects are available from long-term trials.

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

! Aspiration hazard

May be fatal if swallowed and enters airways.

! Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

May cause vomiting.

May irritate the mucosae.

When inhaled, reaction time and coordination sense may be reduced.

Causes eye irritation.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**! General regulation**

Harmful to aquatic life with long lasting effects.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

**Aluminium Paint****SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

08 01 11*

Name of waste

waste paint and varnish containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	Paint
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	III	III	III
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 3

tunnel restriction code D/E

Special provisions 640E

Classification code F1

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

Transport as limited quantities according to 3.4 IMDG Code is possible.

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

No information available.

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312,	-?-
H332	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H411	Toxic to aquatic life with long lasting effects.