

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CEMENT SVS VULC**

Revision date: 06.10.2023

Product code: 00156-0029

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

TIP TOP CEMENT SVS VULC

**Art.-No.**

90008, 90009, 90010, 020004, 020009, 020010, 020011, 020540, 020541, 020542, 020543, 505 0196, 505 4037, 505 4051, 505 9010, 505 9017, 505 9018, 505 9025, 505 9032, 505 9035, 505 9036, 505 9037, 505 9038, 505 9050, 505 9055, 505 9056, 505 9127, 505 9128, 505 9142, 505 9145, 505 9159, 505 9197, 505 9198, 505 9245, 505 9246, 505 9252, 505 9253, 506 0000, 506 0006, 506 0007, 506 0021, 506 0045, 506 0048, 506 0100, 506 0103, 506 0117, 506 0193, 506 0194, 506 0203, 506 0306, 506 0308, 506 0375, 506 0376, 506 0518, 506 0519, 506 0605, 506 0900, 506 0911, 506 0912, 506 1500, 506 4003, 506 4004, 506 4005, 506 4027, 506 4041, 506 4106, 506 4190, 506 4191, 506 4195, 506 4199, 506 4200, 506 4201, 506 4209, 506 4254, 506 4302, 506 4371, 506 4515, 506 4601, 506 8100, 506 9015, 506 9022, 506 9030, 506 9053, 506 9060, 506 9061, 506 9101, 506 9118, 506 9120, 506 9132, 506 9133, 506 9148, 506 9149, 506 9150, 506 9163, 506 9170, 506 9190, 506 9500, 506 9510, 506 9520, 506 9521, 506 9534, 506 9637, 506 9716, 506 9724, 506 9730, 506 9740, 506 9741, 506 9749, 506 9750, 506 9751, 506 9760, 506 9770, 507 0011, 507 0012, 507 0310, 507 0311, 507 0602, 507 0603, 507 9706, 507 9892, 507 9971, 514 8790, 514 8820, 514 8870, 514 8890, 546 2313, 552 3190, 552 3197, 552 3198, 552 3199, 552 4196, 596 4354, 5042, 5042-10, 5054, 5952, 5952-10, 5098-10, 5086, 5087, 5088, 5097, 5098, 5096, 5106, 8823, 8824

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

adhesive

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: REMA TIP TOP AG  
Street: Gruber Strasse 65  
Place: D-85586 Poing  
Telephone: +49 (0) 8121 / 707 - 100  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**Supplier**

Company name: REMA TIP TOP AUTOMOTIVE UK LTD  
Street: Westland Square, LEEDS  
Place: West Yorkshire, LS11 5XS  
Telephone: +44 (0)113 2770044  
E-mail: info@tip-top.co.uk  
Internet: www.rema-tiptop.co.uk

**1.4. Emergency telephone number:**

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 2 of 12

#### GB CLP Regulation

##### Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

##### Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.
P501	Dispose of contents/container to waste treatment facility in accordance with local and national regulations .

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation solved in petroleum spirit

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 3 of 12

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]	< 70 %
	921-024-6	01-2119475514-35
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane]	< 25 %
	931-254-9	01-2119484651-34
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
5459-93-8	N-Cyclohexyl-N-ethylamine	< 2,5 %
	226-733-8	01-2119949285-29
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H226 H311 H332 H302 H314 H318 H412	

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
5459-93-8	226-733-8	N-Cyclohexyl-N-ethylamine	< 2,5 %
		inhalation: ATE = 11 mg/l (vapours); dermal: LD50 = 750 mg/kg; oral: LD50 = 590 mg/kg	

#### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Remove contaminated soaked clothing immediately.  
 In the event of persistent symptoms receive medical treatment.  
 Take away from danger area and lay down affected person.

##### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
 Seek medical treatment immediately.

##### After contact with skin

Wash off immediately with soap and plenty of water.  
 Treat subsequently with skin cream.  
 Consult a doctor if skin irritation persists.

##### After contact with eyes

If eye irritation persists, consult a specialist.  
 Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

##### After ingestion

Do not induce vomiting.  
 Attention. Beware, danger of aspiration.  
 Summon a doctor immediately.  
 Induce vomiting only upon the advice of a physician.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 4 of 12

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Attention. Beware, danger of aspiration.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Use only explosion-proof equipment.  
Ensure adequate ventilation.  
Keep away noninvolved persons.

##### **For non-emergency personnel**

Do not breathe vapours.  
Avoid contact with skin, eyes and clothing.

##### **For emergency responders**

In case of vapour formation use respirator.  
Use personal protective clothing.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 5 of 12

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

- Keep container tightly closed.
- Vapours are heavier than air and spread along ground.
- Use only in thoroughly ventilated areas.
- Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

#### Hints on joint storage

- Incompatible with oxidizing agents.

#### Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

adhesive

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Additional advice on limit values

- To date, no national critical limit values exist.

### 8.2. Exposure controls

#### Appropriate engineering controls

- Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.
- Remove and wash contaminated clothes before re-use.

#### Eye/face protection

- Tightly fitting goggles (EN 166).

#### Hand protection

- Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by [www.kcl.de](http://www.kcl.de).
- This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
- Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

- Solvent-resistant apron (EN 467).

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CEMENT SVS VULC**

Revision date: 06.10.2023

Product code: 00156-0029

Page 6 of 12

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Hydrocarbon-like

**Test method**

pH-Value:	n.d.
-----------	------

**Changes in the physical state**

Melting point/freezing point:	< - 50 °C *)
Boiling point or initial boiling point and boiling range:	> 60 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 25 °C DIN EN ISO 3679
Sustaining combustion:	Sustaining combustion

**Flammability**

Solid/liquid:	n.a.
---------------	------

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	0,8 vol. % *)
Upper explosion limits:	8,0 vol. % *)
Auto-ignition temperature:	260 °C *)

**Self-ignition temperature**

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

**Oxidizing properties**

Not oxidising.

Vapour pressure: (at 20 °C)	190 hPa *)
--------------------------------	------------

Density (at 20 °C):	0,72 g/cm <sup>3</sup>
---------------------	------------------------

Bulk density:	n.a.
---------------	------

Water solubility: (at 20 °C)	Immiscible
---------------------------------	------------

**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water:	n.d.
--	------

Viscosity / dynamic:	2900 - 3500 mPa·s
----------------------	-------------------

Viscosity / kinematic: (at 40 °C)	2485 - 2535 mm <sup>2</sup> /s
--------------------------------------	--------------------------------

Flow time: (at 23 °C)	108 s 6 DIN EN ISO 2431
--------------------------	-------------------------

Relative vapour density:	n.d.
--------------------------	------

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CEMENT SVS VULC**

Revision date: 06.10.2023

Product code: 00156-0029

Page 7 of 12

Evaporation rate:	n.d.
Solvent separation test:	0 %
Solvent content:	> 90 %

**9.2. Other information**

\*) Naphtha (petroleum)

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

**10.5. Incompatible materials**

oxidizing agents

**10.6. Hazardous decomposition products**

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.  
Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Naphtha (petroleum)  
LD<sub>50</sub>/oral/rat: > 2000 mg/kg  
LD<sub>50</sub>/dermal/rabbit: > 2000 mg/kg  
LC<sub>50</sub>/inhalation/rat: > 20 mg/l

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]; Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane])



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 8 of 12

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **11.2. Information on other hazards**

##### **Endocrine disrupting properties**

No data available

##### **Other information**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

A longer or repeated contact may lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

### **SECTION 12: Ecological information**

#### **12.1. Toxicity**

Ecological data are not available.

Naphtha (petroleum)

EC50/Daphnia: 1 - 10 mg/l

EC50/Algae: 10 - 100 mg/l

N-Cyclohexyl-N-ethylamine

EC50/Daphnia magna/48 h = 10 - 100 mg/l

ErC50/Desmodesmus subspicatus/72 h = 10 - 100 mg/l

Toxic to aquatic life with long lasting effects.

#### **12.2. Persistence and degradability**

No data available

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

Low hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 9 of 12

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** ADHESIVES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
Transport category: 3  
Tunnel restriction code: E

#### Other applicable information (land transport)

Receptacle max. 450 L, ADR subsection 2.2.3.1.4  
HAZCHEM: 3YE

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1

#### Marine transport (IMDG)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** ADHESIVES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP CEMENT SVS VULC

Revision date: 06.10.2023

Product code: 00156-0029

Page 10 of 12



Marine pollutant: Yes  
Special Provisions: 223, 955  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-D

#### Other applicable information (marine transport)

Receptacle max. 450 L, IMDG Code subsection 2.3.2.2

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** ADHESIVES  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 30 L (\*)  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 100 L (\*)

#### Other applicable information (air transport)

\*) [3.3.3.1 IATA DGR]

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2004/42/EC (VOC): &lt; 95 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CEMENT SVS VULC**

Revision date: 06.10.2023

Product code: 00156-0029

Page 11 of 12

Additional information: E2

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1.

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP CEMENT SVS VULC**

Revision date: 06.10.2023

Product code: 00156-0029

Page 12 of 12

H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*