SAFETY DATA SHEET



WEICON Casting Resin MS 1000 Hardener

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name UFI Product code Color : WEICON Casting Resin MS 1000 Hardener

: 🗚51-80QY-C00H-NUG0

: 105202

: Yellowish.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Hardener for resins.	

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG Königsberger Str. 255 48157 Münster Germany Phone: +49 251 93220 Fax: +49(0)251 / 9322 - 244 Internet: www.weicon.de e-mail address of person : msds@weicon.de responsible for this SDS

1.4 Emergency telephone number

Telephone number: EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333
(English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44
1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

SECTION 2: Hazards		
Hazard statements	:	₩314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	 Wear protective gloves, protective clothing and eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapor.
Response	:	 P391 - Collect spillage. P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several
		minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	₽405 - Store locked up.
Disposal	:	P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	:	Reaction mass of trientine and trientine, mono- and di-propoxylated 3,6-diazaoctanethylenediamin
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Reaction mass of trientine and trientine, mono- and di- propoxylated	REACH #: 01-2120098765-38 EC: 942-835-1 CAS: -	≥75 - ≤90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	[1]
3,6-diazaoctanethylenediamin	REACH #: pre-registered EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥10 - ≤25	Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1] [2]

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid m	easures
Eye contact	: Cet medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Set medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Set medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Set medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>

SECTION 4: First aid measures

Eye contact	: Adverse symptoms may include the following:	
	pain	
	watering	
	redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following:	
	pain or irritation	
	redness	
	blistering may occur	
I		
Ingestion	: Adverse symptoms may include the following:	
	stomach pains	

4.5 indication of any inimediate medical attention and special treatment needed		
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	: No specific treatment.	

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising f	fron	n the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel i No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders i If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision

SECTION 6: Accidental release measures

6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused
	environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and materials for containment and cleaning up	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteriaCategoryNotification and MAPP
thresholdSafety report thresholdE2200 tonne500 tonne

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values		
3 ,6-diazaoctanethylenediamin	DFG MAC-values list (Germany, 8/2020). Skin sensitizer.		

Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
--	--

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls	: Fuser operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	ures
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

Other skin protection	propriate footwear and any additional skin prote lected based on the task being performed and t proved by a specialist before handling this prod	he risks involved and should be
Respiratory protection	used on the hazard and potential for exposure, s propriate standard or certification. Respirators spiratory protection program to ensure proper fit pects of use. Recommended : organic vapor (must be used according to a ting, training, and other important
Environmental exposure controls	nissions from ventilation or work process equipr sure they comply with the requirements of envir some cases, fume scrubbers, filters or engineer uipment will be necessary to reduce emissions	onmental protection legislation. ring modifications to the process

SECTION 9: Physical and chemical properties

9.1 Information on basic physica	l ai	nd chemical properties					
<u>Appearance</u>							
Physical state	: Liquid.						
Color	: 🖌ellowish.						
Odor	:	Alkaline.					
Odor threshold	:	Not available.					
Melting point/freezing point	:	Not available.					
Initial boiling point and boiling range	:	>200°C (>392°F)					
Flammability (solid, gas)	:	Fammable in the presence of sparks and static discharge. Slightly flammable in the prese	-				
Upper/lower flammability or explosive limits	:	Not available.					
Flash point	:	C losed cup: >100°C (>212°F)					
Auto-ignition temperature	:	Ingredient name	°C	°F	Method		
		3,6-diazaoctanethylenediamin	337,78	640			
Decomposition temperature	:	Not available.					
рН	:	Not applicable.					
Viscosity	:	Not available.					
Solubility(ies)	:	Not available.					
Solubility in water	:	Not available.					
Miscible with water	:	: No.					
Partition coefficient: n-octanol/ water	:	Not applicable.					
Vapor pressure	:	Ø,0001 kPa (0,00075006 mm l	Hg)				
Evaporation rate	:	Not available.					
Relative density	:	Not available.					
Density	:	1,02 g/cm³ [20°C (68°F)]					
Vapor density	:	Not available.					
Explosive properties	1	Not available.					
Oxidizing properties	: Not available.						
Particle characteristics							
Median particle size	:	Not applicable.					
9.2 Other information							
SADT	:	Not available.					
Date of issue/Date of revision	: 30	0.09.2021 Date of previous issue	: 10.08.2	2021	Version	: 3.01	7/14

SECTION 9: Physical and chemical properties				
SAPT	: Not available.			
SECTION 10: Stabili	ity and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
WEICON Casting Resin MS 1000 Hardener	LD50 Dermal	Rat	>2150 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	805 mg/kg	-
	LD50 Oral	Rat	2500 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Route	ATE value
Oral	4500 mg/kg

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observatio
3,6-diazaoctanethylenediamin	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Eyes - Severe irritant	Rabbit	-	49 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 5	-
				mg	
	Skin - Severe irritant	Rabbit	-	490 mg	-
Conclusion/Summary	: Not available.				
<u>Sensitization</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
<u>Carcinogenicity</u>					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
ate of issue/Date of revision	: 30.09.2021 Date of previo	us issue : 10	.08.2021	Vers	ion : 3.01

SECTION 11: Toxico	-
Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.
Specific target organ toxici	ity (single exposure)
Not available.	
<u>Specific target organ toxici</u> Not available.	ity (repeated exposure)
Aspiration hazard Not available.	
Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>s</u>
Eye contact	: 🗭auses serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: 🗭auses severe burns. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
O	
	ysical, chemical and toxicological characteristics
Eye contact	 Adverse symptoms may include the following: pain watering
	redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	 Adverse symptoms may include the following: stomach pains
Delayed and immediate effer Short term exposure	cts and also chronic effects from short and long term exposure
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	iects
Not available.	
	: Not available.
Conclusion/Summary	
Conclusion/Summary General	 Not available. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
-	: Once sensitized, a severe allergic reaction may occur when subsequently exposed
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
General Carcinogenicity	 Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. No known significant effects or critical hazards.

Date of issue/Date of revision

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 - Germany

WEICON Casting Resin MS 1000 Hardener

SECTION 11: Toxicological information

Fertility effects

: No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
WEICON Casting Resin MS 1000 Hardener	EC50 4,1 mg/l	Algae	72 hours
	EC50 48 mg/l	Daphnia	48 hours
	LC50 >4,1 mg/l	Fish	96 hours
3,6-diazaoctanethylenediamin	Acute EC50 3700 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute LC50 33900 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
Conclusion/Summary	: Not available.		

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
WEICON Casting Resin MS 1000 Hardener	-	4 % - Not readily - 28 days	100 mg/l	-

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	low

12.4 Mobility	in	soil
---------------	----	------

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
---------------------	--

Date of issue/Date of revision	: 30.09.2021	Date of previous issue	: 10.08.2021	Version : 3.01	10/14
--------------------------------	--------------	------------------------	--------------	----------------	-------

Hazardous waste

SECTION 13: Disposal considerations

: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
Packaging		
Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 	
Type of packaging	European waste catalogue (EWC)	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	
Special precautions	 This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. 	

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of trientine and trientine, mono- and di-propoxylated)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction mass of trientine and trientine, mono- and di-propoxylated)	Environmentally hazardous substance, liquid, n.o.s. (Reaction mass of trientine and trientine, mono- and di- propoxylated)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group		111	111
14.5 Environmental hazards	Yes. Reaction mass of trientine and trientine, mono- and di- propoxylated	Yes. Reaction mass of trientine and trientine, mono- and di- propoxylated	Yes.
Additional informa ADR/RID	: This product is not or ≤5 kg, provided t and 4.1.1.4 to 4.1.1 <u>Hazard identificati</u> <u>Limited quantity</u> 5	<u>on number</u> 90 L ፮ 274, 335, 601, 375	
IMDG		regulated as a dangerous good w	/hen transported in sizes of <

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
 Emergency schedules F-A, S-F
 Special provisions 274, 335, 969

SECTION 14: Transport information

ΙΑΤΑ	 This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. <u>Quantity limitation</u> Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y964.
14.6 Special precautions for user	 Special provisions A97, A158, A197 Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to IMO instruments	: Not available.
SECTION 15: Regula	tory information

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles
Other EU regulations
Industrial emissions : Not listed (integrated pollution prevention and control) - Air
Industrial emissions : Not listed (integrated pollution prevention and control) - Water
Ozone depleting substances (1005/2009/EU)
Not listed.
Prior Informed Consent (PIC) (649/2012/EU) Not listed.
Persistent Organic Pollutants Not listed.
Seveso Directive
This product is controlled under the Seveso Directive.
Danger criteria
Category
E2
National regulations

Date of issue/Date of revision

: 30.09.2021 Date of previous issue

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 - Germany

WEICON Casting Resin MS 1000 Hardener

SECTION 15: Regulatory information

Storage class (TRGS 510) : BA

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

<u>Danger criteria</u>

Category	Reference number
E2	1.3.2

Hazard class for water Technical instruction on

: **F**A-Luft Number 5.2.5: 61-100%

air quality control International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

: 2

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: Not determined.
Canada	: Not determined.
China	: Not determined.
Europe	: All components are listed or exempted.
Japan	: Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical Safety: This product contains substances for which Chemical Safety Assessments are still
required.

SECTION 16: Other information

Indicates information the	at has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
Date of issue/Date of revision	: 30.09.2021 Date of previous issue : 10.08.2021 Version : 3.01 13/14

SECTION 16: Other information

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

⊮ 312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Date of printing	: 30.09.2021			
Skin Sens. 1B		SKIN SENSITIZATION - Category 1B		
Skin Sens. 1		SKIN SENSITIZATION - Category 1		
Skin Irrit. 2		SKIN CORROSION/IRRITATION - Category 2		
Skin Corr. 1B		SKIN CORROSION/IRRITATION - Category 1B		
Eye Irrit. 2		SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2		
Eye Dam. 1		SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1		
Aquatic Chronic 3		AQUATIC HAZARD (LONG-TERM) - Category 3		
Aquatic Chronic 2		AQUATIC HAZARD (LONG-TERM) - Category 2		
Acute Tox. 4		ACUTE TOXICITY - Category 4		

•	00.00.2021
:	30.09.2021
:	10.08.2021
:	3.01
	:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.