

品番：EA940AG-501

品名：0.75mm² x 5m / 2芯 ビニルキャブタイヤケーブル



販売価格	1,260円(税抜) / 1,386円(税込)		
カタログ価格	1,260円(税抜) / 1,386円(税込)		
在庫数	最新在庫: 11 (2026/06/23 03:45現在)		
商品入数	1	販売単位	本
カタログページ	1137ページ		



規格	外径	芯数
2.0mm	2.0	2
2.5mm	2.5	2
3.0mm	3.0	2
3.5mm	3.5	2
4.0mm	4.0	2
4.5mm	4.5	2
5.0mm	5.0	2
5.5mm	5.5	2
6.0mm	6.0	2
6.5mm	6.5	2
7.0mm	7.0	2
7.5mm	7.5	2
8.0mm	8.0	2
8.5mm	8.5	2
9.0mm	9.0	2
9.5mm	9.5	2
10.0mm	10.0	2
10.5mm	10.5	2
11.0mm	11.0	2
11.5mm	11.5	2
12.0mm	12.0	2
12.5mm	12.5	2
13.0mm	13.0	2
13.5mm	13.5	2
14.0mm	14.0	2
14.5mm	14.5	2
15.0mm	15.0	2
15.5mm	15.5	2
16.0mm	16.0	2
16.5mm	16.5	2
17.0mm	17.0	2
17.5mm	17.5	2
18.0mm	18.0	2
18.5mm	18.5	2
19.0mm	19.0	2
19.5mm	19.5	2
20.0mm	20.0	2
20.5mm	20.5	2
21.0mm	21.0	2
21.5mm	21.5	2
22.0mm	22.0	2
22.5mm	22.5	2
23.0mm	23.0	2
23.5mm	23.5	2
24.0mm	24.0	2
24.5mm	24.5	2
25.0mm	25.0	2
25.5mm	25.5	2
26.0mm	26.0	2
26.5mm	26.5	2
27.0mm	27.0	2
27.5mm	27.5	2
28.0mm	28.0	2
28.5mm	28.5	2
29.0mm	29.0	2
29.5mm	29.5	2
30.0mm	30.0	2
30.5mm	30.5	2
31.0mm	31.0	2
31.5mm	31.5	2
32.0mm	32.0	2
32.5mm	32.5	2
33.0mm	33.0	2
33.5mm	33.5	2
34.0mm	34.0	2
34.5mm	34.5	2
35.0mm	35.0	2
35.5mm	35.5	2
36.0mm	36.0	2
36.5mm	36.5	2
37.0mm	37.0	2
37.5mm	37.5	2
38.0mm	38.0	2
38.5mm	38.5	2
39.0mm	39.0	2
39.5mm	39.5	2
40.0mm	40.0	2
40.5mm	40.5	2
41.0mm	41.0	2
41.5mm	41.5	2
42.0mm	42.0	2
42.5mm	42.5	2
43.0mm	43.0	2
43.5mm	43.5	2
44.0mm	44.0	2
44.5mm	44.5	2
45.0mm	45.0	2
45.5mm	45.5	2
46.0mm	46.0	2
46.5mm	46.5	2
47.0mm	47.0	2
47.5mm	47.5	2
48.0mm	48.0	2
48.5mm	48.5	2
49.0mm	49.0	2
49.5mm	49.5	2
50.0mm	50.0	2
50.5mm	50.5	2
51.0mm	51.0	2
51.5mm	51.5	2
52.0mm	52.0	2
52.5mm	52.5	2
53.0mm	53.0	2
53.5mm	53.5	2
54.0mm	54.0	2
54.5mm	54.5	2
55.0mm	55.0	2
55.5mm	55.5	2
56.0mm	56.0	2
56.5mm	56.5	2
57.0mm	57.0	2
57.5mm	57.5	2
58.0mm	58.0	2
58.5mm	58.5	2
59.0mm	59.0	2
59.5mm	59.5	2
60.0mm	60.0	2
60.5mm	60.5	2
61.0mm	61.0	2
61.5mm	61.5	2
62.0mm	62.0	2
62.5mm	62.5	2
63.0mm	63.0	2
63.5mm	63.5	2
64.0mm	64.0	2
64.5mm	64.5	2
65.0mm	65.0	2
65.5mm	65.5	2
66.0mm	66.0	2
66.5mm	66.5	2
67.0mm	67.0	2
67.5mm	67.5	2
68.0mm	68.0	2
68.5mm	68.5	2
69.0mm	69.0	2
69.5mm	69.5	2
70.0mm	70.0	2
70.5mm	70.5	2
71.0mm	71.0	2
71.5mm	71.5	2
72.0mm	72.0	2
72.5mm	72.5	2
73.0mm	73.0	2
73.5mm	73.5	2
74.0mm	74.0	2
74.5mm	74.5	2
75.0mm	75.0	2
75.5mm	75.5	2
76.0mm	76.0	2
76.5mm	76.5	2
77.0mm	77.0	2
77.5mm	77.5	2
78.0mm	78.0	2
78.5mm	78.5	2
79.0mm	79.0	2
79.5mm	79.5	2
80.0mm	80.0	2
80.5mm	80.5	2
81.0mm	81.0	2
81.5mm	81.5	2
82.0mm	82.0	2
82.5mm	82.5	2
83.0mm	83.0	2
83.5mm	83.5	2
84.0mm	84.0	2
84.5mm	84.5	2
85.0mm	85.0	2
85.5mm	85.5	2
86.0mm	86.0	2
86.5mm	86.5	2
87.0mm	87.0	2
87.5mm	87.5	2
88.0mm	88.0	2
88.5mm	88.5	2
89.0mm	89.0	2
89.5mm	89.5	2
90.0mm	90.0	2
90.5mm	90.5	2
91.0mm	91.0	2
91.5mm	91.5	2
92.0mm	92.0	2
92.5mm	92.5	2
93.0mm	93.0	2
93.5mm	93.5	2
94.0mm	94.0	2
94.5mm	94.5	2
95.0mm	95.0	2
95.5mm	95.5	2
96.0mm	96.0	2
96.5mm	96.5	2
97.0mm	97.0	2
97.5mm	97.5	2
98.0mm	98.0	2
98.5mm	98.5	2
99.0mm	99.0	2
99.5mm	99.5	2
100.0mm	100.0	2

電線の太さ(芯数)	電線の電圧(VCT/VCTGPNCT)
2.0mm(2)	22(20)
※ $x30$	19(20)
※ $x40$	17(20)
3.5mm(2)	32(41)
※ $x30$	28(30)
※ $x40$	25(32)
5.5mm(2)	41(53)
※ $x30$	36(40)
※ $x40$	32(42)
8.0mm(2)	51(65)
※ $x30$	44(50)
※ $x40$	39(50)
14.0mm(2)	71(91)
※ $x30$	62(80)
※ $x40$	55(71)

仕様

略号	VCT	用途	600V以下の移動用電気機器用
定格容量	14A 600V (0.75mm ² x 2心)	長さ	5m
公称断面積	0.75mm ²	仕上外径	8.8mm
曲げ半径	36mm以上	定格温度	移動:-15~60℃ 固定:-30~60℃

耐熱性ビニル絶縁ソフトビニルシースキャブタイヤケーブル

2心(白・黒)

柔軟性、耐熱性、難燃性に優れます

一般的なVCTに比べ柔軟性に優れ、取り回しが良好です。

据え置き-30℃までの耐寒性で、寒冷地や冷凍庫内の配線に最適です。

PSEマーク取得商品

代替品

品番	EA940AG-502
コメント	10m



株式会社エスコ

大阪府大阪市西区立売堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.