

品番：**EA940AG-676**

品名：3.5 mm²x20m/4芯 ビニルキャブタイヤケーブル



販売価格	19,000円 (税抜) / 20,900円(税込)		
カタログ価格	19,000円(税抜) / 20,900円(税込)		
在庫数	最新在庫: 0 (2026/06/23 04:58現在)		
商品入数	1	販売単位	本
カタログページ	1137ページ		



電線の太さ(心数)	電線許容電流(AI) VCT/2CT/3PHCT
2.0mm ² ×20	22(28)
φ ×30	19(24)
φ ×40	17(22)
3.5mm ² ×20	32(41)
φ ×30	28(36)
φ ×40	25(32)
5.0mm ² ×20	41(53)
φ ×30	36(46)
φ ×40	32(42)
8.0mm ² ×20	51(65)
φ ×30	44(56)
φ ×40	39(50)
14.0mm ² ×20	71(91)
φ ×30	62(80)
φ ×40	55(71)

品名	規格	長さ	心数	外径	重量
VCT-CAB-20-2	2.0mm ² ×20	20m	2	φ14.0	0.12
VCT-CAB-20-3	2.0mm ² ×20	20m	3	φ14.0	0.15
VCT-CAB-20-4	2.0mm ² ×20	20m	4	φ14.0	0.18
VCT-CAB-20-5	2.0mm ² ×20	20m	5	φ14.0	0.21
VCT-CAB-20-6	2.0mm ² ×20	20m	6	φ14.0	0.24
VCT-CAB-20-7	2.0mm ² ×20	20m	7	φ14.0	0.27
VCT-CAB-20-8	2.0mm ² ×20	20m	8	φ14.0	0.30
VCT-CAB-20-9	2.0mm ² ×20	20m	9	φ14.0	0.33
VCT-CAB-20-10	2.0mm ² ×20	20m	10	φ14.0	0.36
VCT-CAB-20-11	2.0mm ² ×20	20m	11	φ14.0	0.39
VCT-CAB-20-12	2.0mm ² ×20	20m	12	φ14.0	0.42
VCT-CAB-20-13	2.0mm ² ×20	20m	13	φ14.0	0.45
VCT-CAB-20-14	2.0mm ² ×20	20m	14	φ14.0	0.48
VCT-CAB-20-15	2.0mm ² ×20	20m	15	φ14.0	0.51
VCT-CAB-20-16	2.0mm ² ×20	20m	16	φ14.0	0.54
VCT-CAB-20-17	2.0mm ² ×20	20m	17	φ14.0	0.57
VCT-CAB-20-18	2.0mm ² ×20	20m	18	φ14.0	0.60
VCT-CAB-20-19	2.0mm ² ×20	20m	19	φ14.0	0.63
VCT-CAB-20-20	2.0mm ² ×20	20m	20	φ14.0	0.66
VCT-CAB-20-21	2.0mm ² ×20	20m	21	φ14.0	0.69
VCT-CAB-20-22	2.0mm ² ×20	20m	22	φ14.0	0.72
VCT-CAB-20-23	2.0mm ² ×20	20m	23	φ14.0	0.75
VCT-CAB-20-24	2.0mm ² ×20	20m	24	φ14.0	0.78
VCT-CAB-20-25	2.0mm ² ×20	20m	25	φ14.0	0.81
VCT-CAB-20-26	2.0mm ² ×20	20m	26	φ14.0	0.84
VCT-CAB-20-27	2.0mm ² ×20	20m	27	φ14.0	0.87
VCT-CAB-20-28	2.0mm ² ×20	20m	28	φ14.0	0.90
VCT-CAB-20-29	2.0mm ² ×20	20m	29	φ14.0	0.93
VCT-CAB-20-30	2.0mm ² ×20	20m	30	φ14.0	0.96
VCT-CAB-20-31	2.0mm ² ×20	20m	31	φ14.0	0.99
VCT-CAB-20-32	2.0mm ² ×20	20m	32	φ14.0	1.02
VCT-CAB-20-33	2.0mm ² ×20	20m	33	φ14.0	1.05
VCT-CAB-20-34	2.0mm ² ×20	20m	34	φ14.0	1.08
VCT-CAB-20-35	2.0mm ² ×20	20m	35	φ14.0	1.11
VCT-CAB-20-36	2.0mm ² ×20	20m	36	φ14.0	1.14
VCT-CAB-20-37	2.0mm ² ×20	20m	37	φ14.0	1.17
VCT-CAB-20-38	2.0mm ² ×20	20m	38	φ14.0	1.20
VCT-CAB-20-39	2.0mm ² ×20	20m	39	φ14.0	1.23
VCT-CAB-20-40	2.0mm ² ×20	20m	40	φ14.0	1.26
VCT-CAB-20-41	2.0mm ² ×20	20m	41	φ14.0	1.29
VCT-CAB-20-42	2.0mm ² ×20	20m	42	φ14.0	1.32
VCT-CAB-20-43	2.0mm ² ×20	20m	43	φ14.0	1.35
VCT-CAB-20-44	2.0mm ² ×20	20m	44	φ14.0	1.38
VCT-CAB-20-45	2.0mm ² ×20	20m	45	φ14.0	1.41
VCT-CAB-20-46	2.0mm ² ×20	20m	46	φ14.0	1.44
VCT-CAB-20-47	2.0mm ² ×20	20m	47	φ14.0	1.47
VCT-CAB-20-48	2.0mm ² ×20	20m	48	φ14.0	1.50
VCT-CAB-20-49	2.0mm ² ×20	20m	49	φ14.0	1.53
VCT-CAB-20-50	2.0mm ² ×20	20m	50	φ14.0	1.56
VCT-CAB-20-51	2.0mm ² ×20	20m	51	φ14.0	1.59
VCT-CAB-20-52	2.0mm ² ×20	20m	52	φ14.0	1.62
VCT-CAB-20-53	2.0mm ² ×20	20m	53	φ14.0	1.65
VCT-CAB-20-54	2.0mm ² ×20	20m	54	φ14.0	1.68
VCT-CAB-20-55	2.0mm ² ×20	20m	55	φ14.0	1.71
VCT-CAB-20-56	2.0mm ² ×20	20m	56	φ14.0	1.74
VCT-CAB-20-57	2.0mm ² ×20	20m	57	φ14.0	1.77
VCT-CAB-20-58	2.0mm ² ×20	20m	58	φ14.0	1.80
VCT-CAB-20-59	2.0mm ² ×20	20m	59	φ14.0	1.83
VCT-CAB-20-60	2.0mm ² ×20	20m	60	φ14.0	1.86
VCT-CAB-20-61	2.0mm ² ×20	20m	61	φ14.0	1.89
VCT-CAB-20-62	2.0mm ² ×20	20m	62	φ14.0	1.92
VCT-CAB-20-63	2.0mm ² ×20	20m	63	φ14.0	1.95
VCT-CAB-20-64	2.0mm ² ×20	20m	64	φ14.0	1.98
VCT-CAB-20-65	2.0mm ² ×20	20m	65	φ14.0	2.01
VCT-CAB-20-66	2.0mm ² ×20	20m	66	φ14.0	2.04
VCT-CAB-20-67	2.0mm ² ×20	20m	67	φ14.0	2.07
VCT-CAB-20-68	2.0mm ² ×20	20m	68	φ14.0	2.10
VCT-CAB-20-69	2.0mm ² ×20	20m	69	φ14.0	2.13
VCT-CAB-20-70	2.0mm ² ×20	20m	70	φ14.0	2.16
VCT-CAB-20-71	2.0mm ² ×20	20m	71	φ14.0	2.19
VCT-CAB-20-72	2.0mm ² ×20	20m	72	φ14.0	2.22
VCT-CAB-20-73	2.0mm ² ×20	20m	73	φ14.0	2.25
VCT-CAB-20-74	2.0mm ² ×20	20m	74	φ14.0	2.28
VCT-CAB-20-75	2.0mm ² ×20	20m	75	φ14.0	2.31
VCT-CAB-20-76	2.0mm ² ×20	20m	76	φ14.0	2.34
VCT-CAB-20-77	2.0mm ² ×20	20m	77	φ14.0	2.37
VCT-CAB-20-78	2.0mm ² ×20	20m	78	φ14.0	2.40
VCT-CAB-20-79	2.0mm ² ×20	20m	79	φ14.0	2.43
VCT-CAB-20-80	2.0mm ² ×20	20m	80	φ14.0	2.46
VCT-CAB-20-81	2.0mm ² ×20	20m	81	φ14.0	2.49
VCT-CAB-20-82	2.0mm ² ×20	20m	82	φ14.0	2.52
VCT-CAB-20-83	2.0mm ² ×20	20m	83	φ14.0	2.55
VCT-CAB-20-84	2.0mm ² ×20	20m	84	φ14.0	2.58
VCT-CAB-20-85	2.0mm ² ×20	20m	85	φ14.0	2.61
VCT-CAB-20-86	2.0mm ² ×20	20m	86	φ14.0	2.64
VCT-CAB-20-87	2.0mm ² ×20	20m	87	φ14.0	2.67
VCT-CAB-20-88	2.0mm ² ×20	20m	88	φ14.0	2.70
VCT-CAB-20-89	2.0mm ² ×20	20m	89	φ14.0	2.73
VCT-CAB-20-90	2.0mm ² ×20	20m	90	φ14.0	2.76
VCT-CAB-20-91	2.0mm ² ×20	20m	91	φ14.0	2.79
VCT-CAB-20-92	2.0mm ² ×20	20m	92	φ14.0	2.82
VCT-CAB-20-93	2.0mm ² ×20	20m	93	φ14.0	2.85
VCT-CAB-20-94	2.0mm ² ×20	20m	94	φ14.0	2.88
VCT-CAB-20-95	2.0mm ² ×20	20m	95	φ14.0	2.91
VCT-CAB-20-96	2.0mm ² ×20	20m	96	φ14.0	2.94
VCT-CAB-20-97	2.0mm ² ×20	20m	97	φ14.0	2.97
VCT-CAB-20-98	2.0mm ² ×20	20m	98	φ14.0	3.00
VCT-CAB-20-99	2.0mm ² ×20	20m	99	φ14.0	3.03
VCT-CAB-20-100	2.0mm ² ×20	20m	100	φ14.0	3.06

仕様

略号	VCT	用途	工事現場などに使用する600V以下の移動用電気機器の電源や配線などに。
定格容量	25A 600V (3.5mm ² ×4心)	長さ	20m
公称断面積	3.5mm ²	仕上外径	14.0mm
定格温度	60℃		

ビニル絶縁ビニルシースキャブタイヤケーブル			
4心(白・黒・赤・緑)			
可とう性にすぐれています。			
PSEマーク取得商品			

株式会社エスコ

大阪府大阪市西区立売堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.