

品番：**EA940AG-682**

品名：8mm²x10m/4芯 ビニルキャブタイヤケーブル



販売価格	25,900円 (税抜) / 28,490円(税込)		
カタログ価格	25,900円(税抜) / 28,490円(税込)		
在庫数	最新在庫: 1 (2026/06/23 06:00現在)		
商品入数	1	販売単位	本
カタログページ	1137ページ		



電線の太さ(心数)	電線許容電流(A) VCT/VCT2(C/N/C/T)
2.0mm ² ×20	22(28)
φ×30	19(24)
φ×40	17(22)
3.0mm ² ×20	32(41)
φ×30	28(36)
φ×40	25(32)
5.0mm ² ×20	41(53)
φ×30	36(46)
φ×40	32(42)
8.0mm ² ×20	51(65)
φ×30	44(56)
φ×40	39(50)
14.0mm ² ×20	71(91)
φ×30	62(79)
φ×40	55(71)

品名	規格	長さ	心数	電線太さ	仕上外径	重量
VCT-CAB-1000	VCT-CAB	10m	2	2.0mm ²	19.5mm	0.15kg
VCT-CAB-1000	VCT-CAB	10m	3	2.0mm ²	21.5mm	0.18kg
VCT-CAB-1000	VCT-CAB	10m	4	2.0mm ²	23.5mm	0.21kg
VCT-CAB-1000	VCT-CAB	10m	5	2.0mm ²	25.5mm	0.24kg
VCT-CAB-1000	VCT-CAB	10m	6	2.0mm ²	27.5mm	0.27kg
VCT-CAB-1000	VCT-CAB	10m	7	2.0mm ²	29.5mm	0.30kg
VCT-CAB-1000	VCT-CAB	10m	8	2.0mm ²	31.5mm	0.33kg
VCT-CAB-1000	VCT-CAB	10m	9	2.0mm ²	33.5mm	0.36kg
VCT-CAB-1000	VCT-CAB	10m	10	2.0mm ²	35.5mm	0.39kg
VCT-CAB-1000	VCT-CAB	10m	12	2.0mm ²	39.5mm	0.45kg
VCT-CAB-1000	VCT-CAB	10m	14	2.0mm ²	43.5mm	0.51kg
VCT-CAB-1000	VCT-CAB	10m	16	2.0mm ²	47.5mm	0.57kg
VCT-CAB-1000	VCT-CAB	10m	18	2.0mm ²	51.5mm	0.63kg
VCT-CAB-1000	VCT-CAB	10m	20	2.0mm ²	55.5mm	0.69kg
VCT-CAB-1000	VCT-CAB	10m	25	2.0mm ²	69.5mm	0.87kg
VCT-CAB-1000	VCT-CAB	10m	30	2.0mm ²	83.5mm	1.05kg
VCT-CAB-1000	VCT-CAB	10m	35	2.0mm ²	97.5mm	1.23kg
VCT-CAB-1000	VCT-CAB	10m	40	2.0mm ²	111.5mm	1.41kg
VCT-CAB-1000	VCT-CAB	10m	45	2.0mm ²	125.5mm	1.59kg
VCT-CAB-1000	VCT-CAB	10m	50	2.0mm ²	139.5mm	1.77kg
VCT-CAB-1000	VCT-CAB	10m	60	2.0mm ²	167.5mm	2.13kg
VCT-CAB-1000	VCT-CAB	10m	70	2.0mm ²	195.5mm	2.49kg
VCT-CAB-1000	VCT-CAB	10m	80	2.0mm ²	223.5mm	2.85kg
VCT-CAB-1000	VCT-CAB	10m	90	2.0mm ²	251.5mm	3.21kg
VCT-CAB-1000	VCT-CAB	10m	100	2.0mm ²	279.5mm	3.57kg
VCT-CAB-1000	VCT-CAB	10m	120	2.0mm ²	343.5mm	4.29kg
VCT-CAB-1000	VCT-CAB	10m	140	2.0mm ²	407.5mm	5.01kg
VCT-CAB-1000	VCT-CAB	10m	160	2.0mm ²	471.5mm	5.73kg
VCT-CAB-1000	VCT-CAB	10m	180	2.0mm ²	535.5mm	6.45kg
VCT-CAB-1000	VCT-CAB	10m	200	2.0mm ²	599.5mm	7.17kg
VCT-CAB-1000	VCT-CAB	10m	250	2.0mm ²	763.5mm	8.89kg
VCT-CAB-1000	VCT-CAB	10m	300	2.0mm ²	927.5mm	10.61kg
VCT-CAB-1000	VCT-CAB	10m	350	2.0mm ²	1091.5mm	12.33kg
VCT-CAB-1000	VCT-CAB	10m	400	2.0mm ²	1255.5mm	14.05kg
VCT-CAB-1000	VCT-CAB	10m	450	2.0mm ²	1419.5mm	15.77kg
VCT-CAB-1000	VCT-CAB	10m	500	2.0mm ²	1583.5mm	17.49kg
VCT-CAB-1000	VCT-CAB	10m	600	2.0mm ²	1947.5mm	21.15kg
VCT-CAB-1000	VCT-CAB	10m	700	2.0mm ²	2311.5mm	24.81kg
VCT-CAB-1000	VCT-CAB	10m	800	2.0mm ²	2675.5mm	28.47kg
VCT-CAB-1000	VCT-CAB	10m	900	2.0mm ²	3039.5mm	32.13kg
VCT-CAB-1000	VCT-CAB	10m	1000	2.0mm ²	3403.5mm	35.79kg

仕様

略号	VCT	用途	工事現場などに使用する600V以下の移動用電気機器の電源や配線などに。
定格容量	39A 600V (8.0mm ² ×4心)	長さ	10m
公称断面積	8.0mm ²	仕上外径	19.5mm
定格温度	60℃		

ビニル絶縁ビニルシースキャブタイヤケーブル			
4心(白・黒・赤・緑)			
可とう性にすぐれています。			
PSEマーク取得商品			

株式会社エスコ

大阪府大阪市西区立売堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.