



品番 : EA141AT-56

品名 : G 3/4"x20.5mm 雌ねじシステム



販売価格	1,140円(税抜) / 1,254円(税込)		
カタログ価格	1,140円(税抜) / 1,254円(税込)		
在庫数	最新在庫: 5 (2026/04/09 04:50現在)		
商品入数	1	販売単位	個
カタログページ	1042ページ		



ねじ径	長さ	外径	内径	重量
G1/8"	10	10.0	7.0	0.15
G1/8"	15	10.0	7.0	0.25
G1/8"	20	10.0	7.0	0.35
G1/8"	25	10.0	7.0	0.45
G1/8"	30	10.0	7.0	0.55
G1/8"	35	10.0	7.0	0.65
G1/8"	40	10.0	7.0	0.75
G1/8"	45	10.0	7.0	0.85
G1/8"	50	10.0	7.0	0.95
G1/8"	55	10.0	7.0	1.05
G1/8"	60	10.0	7.0	1.15
G1/8"	65	10.0	7.0	1.25
G1/8"	70	10.0	7.0	1.35
G1/8"	75	10.0	7.0	1.45
G1/8"	80	10.0	7.0	1.55
G1/8"	85	10.0	7.0	1.65
G1/8"	90	10.0	7.0	1.75
G1/8"	95	10.0	7.0	1.85
G1/8"	100	10.0	7.0	1.95
G1/8"	105	10.0	7.0	2.05
G1/8"	110	10.0	7.0	2.15
G1/8"	115	10.0	7.0	2.25
G1/8"	120	10.0	7.0	2.35
G1/8"	125	10.0	7.0	2.45
G1/8"	130	10.0	7.0	2.55
G1/8"	135	10.0	7.0	2.65
G1/8"	140	10.0	7.0	2.75
G1/8"	145	10.0	7.0	2.85
G1/8"	150	10.0	7.0	2.95
G1/8"	155	10.0	7.0	3.05
G1/8"	160	10.0	7.0	3.15
G1/8"	165	10.0	7.0	3.25
G1/8"	170	10.0	7.0	3.35
G1/8"	175	10.0	7.0	3.45
G1/8"	180	10.0	7.0	3.55
G1/8"	185	10.0	7.0	3.65
G1/8"	190	10.0	7.0	3.75
G1/8"	195	10.0	7.0	3.85
G1/8"	200	10.0	7.0	3.95
G1/8"	205	10.0	7.0	4.05
G1/8"	210	10.0	7.0	4.15
G1/8"	215	10.0	7.0	4.25
G1/8"	220	10.0	7.0	4.35
G1/8"	225	10.0	7.0	4.45
G1/8"	230	10.0	7.0	4.55
G1/8"	235	10.0	7.0	4.65
G1/8"	240	10.0	7.0	4.75
G1/8"	245	10.0	7.0	4.85
G1/8"	250	10.0	7.0	4.95
G1/8"	255	10.0	7.0	5.05
G1/8"	260	10.0	7.0	5.15
G1/8"	265	10.0	7.0	5.25
G1/8"	270	10.0	7.0	5.35
G1/8"	275	10.0	7.0	5.45
G1/8"	280	10.0	7.0	5.55
G1/8"	285	10.0	7.0	5.65
G1/8"	290	10.0	7.0	5.75
G1/8"	295	10.0	7.0	5.85
G1/8"	300	10.0	7.0	5.95
G1/8"	305	10.0	7.0	6.05
G1/8"	310	10.0	7.0	6.15
G1/8"	315	10.0	7.0	6.25
G1/8"	320	10.0	7.0	6.35
G1/8"	325	10.0	7.0	6.45
G1/8"	330	10.0	7.0	6.55
G1/8"	335	10.0	7.0	6.65
G1/8"	340	10.0	7.0	6.75
G1/8"	345	10.0	7.0	6.85
G1/8"	350	10.0	7.0	6.95
G1/8"	355	10.0	7.0	7.05
G1/8"	360	10.0	7.0	7.15
G1/8"	365	10.0	7.0	7.25
G1/8"	370	10.0	7.0	7.35
G1/8"	375	10.0	7.0	7.45
G1/8"	380	10.0	7.0	7.55
G1/8"	385	10.0	7.0	7.65
G1/8"	390	10.0	7.0	7.75
G1/8"	395	10.0	7.0	7.85
G1/8"	400	10.0	7.0	7.95
G1/8"	405	10.0	7.0	8.05
G1/8"	410	10.0	7.0	8.15
G1/8"	415	10.0	7.0	8.25
G1/8"	420	10.0	7.0	8.35
G1/8"	425	10.0	7.0	8.45
G1/8"	430	10.0	7.0	8.55
G1/8"	435	10.0	7.0	8.65
G1/8"	440	10.0	7.0	8.75
G1/8"	445	10.0	7.0	8.85
G1/8"	450	10.0	7.0	8.95
G1/8"	455	10.0	7.0	9.05
G1/8"	460	10.0	7.0	9.15
G1/8"	465	10.0	7.0	9.25
G1/8"	470	10.0	7.0	9.35
G1/8"	475	10.0	7.0	9.45
G1/8"	480	10.0	7.0	9.55
G1/8"	485	10.0	7.0	9.65
G1/8"	490	10.0	7.0	9.75
G1/8"	495	10.0	7.0	9.85
G1/8"	500	10.0	7.0	9.95
G1/8"	505	10.0	7.0	10.05
G1/8"	510	10.0	7.0	10.15
G1/8"	515	10.0	7.0	10.25
G1/8"	520	10.0	7.0	10.35
G1/8"	525	10.0	7.0	10.45
G1/8"	530	10.0	7.0	10.55
G1/8"	535	10.0	7.0	10.65
G1/8"	540	10.0	7.0	10.75
G1/8"	545	10.0	7.0	10.85
G1/8"	550	10.0	7.0	10.95
G1/8"	555	10.0	7.0	11.05
G1/8"	560	10.0	7.0	11.15
G1/8"	565	10.0	7.0	11.25
G1/8"	570	10.0	7.0	11.35
G1/8"	575	10.0	7.0	11.45
G1/8"	580	10.0	7.0	11.55
G1/8"	585	10.0	7.0	11.65
G1/8"	590	10.0	7.0	11.75
G1/8"	595	10.0	7.0	11.85
G1/8"	600	10.0	7.0	11.95
G1/8"	605	10.0	7.0	12.05
G1/8"	610	10.0	7.0	12.15
G1/8"	615	10.0	7.0	12.25
G1/8"	620	10.0	7.0	12.35
G1/8"	625	10.0	7.0	12.45
G1/8"	630	10.0	7.0	12.55
G1/8"	635	10.0	7.0	12.65
G1/8"	640	10.0	7.0	12.75
G1/8"	645	10.0	7.0	12.85
G1/8"	650	10.0	7.0	12.95
G1/8"	655	10.0	7.0	13.05
G1/8"	660	10.0	7.0	13.15
G1/8"	665	10.0	7.0	13.25
G1/8"	670	10.0	7.0	13.35
G1/8"	675	10.0	7.0	13.45
G1/8"	680	10.0	7.0	13.55
G1/8"	685	10.0	7.0	13.65
G1/8"	690	10.0	7.0	13.75
G1/8"	695	10.0	7.0	13.85
G1/8"	700	10.0	7.0	13.95
G1/8"	705	10.0	7.0	14.05
G1/8"	710	10.0	7.0	14.15
G1/8"	715	10.0	7.0	14.25
G1/8"	720	10.0	7.0	14.35
G1/8"	725	10.0	7.0	14.45
G1/8"	730	10.0	7.0	14.55
G1/8"	735	10.0	7.0	14.65
G1/8"	740	10.0	7.0	14.75
G1/8"	745	10.0	7.0	14.85
G1/8"	750	10.0	7.0	14.95
G1/8"	755	10.0	7.0	15.05
G1/8"	760	10.0	7.0	15.15
G1/8"	765	10.0	7.0	15.25
G1/8"	770	10.0	7.0	15.35
G1/8"	775	10.0	7.0	15.45
G1/8"	780	10.0	7.0	15.55
G1/8"	785	10.0	7.0	15.65
G1/8"	790	10.0	7.0	15.75
G1/8"	795	10.0	7.0	15.85
G1/8"	800	10.0	7.0	15.95
G1/8"	805	10.0	7.0	16.05
G1/8"	810	10.0	7.0	16.15
G1/8"	815	10.0	7.0	16.25
G1/8"	820	10.0	7.0	16.35
G1/8"	825	10.0	7.0	16.45
G1/8"	830	10.0	7.0	16.55
G1/8"	835	10.0	7.0	16.65
G1/8"	840	10.0	7.0	16.75
G1/8"	845	10.0	7.0	16.85
G1/8"	850	10.0	7.0	16.95
G1/8"	855	10.0	7.0	17.05
G1/8"	860	10.0	7.0	17.15
G1/8"	865	10.0	7.0	17.25
G1/8"	870	10.0	7.0	17.35
G1/8"	875	10.0	7.0	17.45
G1/8"	880	10.0	7.0	17.55
G1/8"	885	10.0	7.0	17.65
G1/8"	890	10.0	7.0	17.75
G1/8"	895	10.0	7.0	17.85
G1/8"	900	10.0	7.0	17.95
G1/8"	905	10.0	7.0	18.05
G1/8"	910	10.0	7.0	18.15
G1/8"	915	10.0	7.0	18.25
G1/8"	920	10.0	7.0	18.35
G1/8"	925	10.0	7.0	18.45
G1/8"	930	10.0	7.0	18.55
G1/8"	935	10.0	7.0	18.65
G1/8"	940	10.0	7.0	18.75
G1/8"	945	10.0	7.0	18.85
G1/8"	950	10.0	7.0	18.95
G1/8"	955	10.0	7.0	19.05
G1/8"	960	10.0	7.0	19.15
G1/8"	965	10.0	7.0	19.25
G1/8"	970	10.0	7.0	19.35
G1/8"	975	10.0	7.0	19.45
G1/8"	980	10.0	7.0	19.55
G1/8"	985	10.0	7.0	19.65
G1/8"	990	10.0	7.0	19.75
G1/8"	995	10.0	7.0	19.85
G1/8"	1000	10.0	7.0	19.95

仕様

メーカー	栗田製作所	型番	No.03×3/4N
ねじ径	G3/4"	タケノコ径	20.5mm
適合ホース内径※	19mm	使用圧力	1.0MPa
使用温度範囲	-5~60℃	材質	真鍮

※適合ホース内径はホース材質により多少誤差が生じます。

株式会社エスコ

大阪府大阪市西区立売堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.