


品番 : EA425CF-102

品名 : R 1/4"x10mm ユニオン(エルボ` /ステンス製)




販売価格	2,790円(税抜) / 3,069円(税込)		
カタログ価格	2,790円(税抜) / 3,069円(税込)		
在庫数	最新在庫: 3 (2026/06/13 04:56現在)		
商品入数	1	販売単位	個
カタログページ	1024ページ		



● 管継手の仕様管理方法
● 使用温度: -196℃~600℃
● 適用圧力: 10MPa(100kgf/cm²)

規格	材質	外径	長さ	重量
R1/4	SUS316	10	20	0.015
R1/2	SUS316	15	25	0.025
R3/4	SUS316	20	30	0.045
R1	SUS316	25	35	0.075
R1.5	SUS316	35	45	0.15
R2	SUS316	45	55	0.25
R2.5	SUS316	55	65	0.4
R3	SUS316	65	75	0.6
R3.5	SUS316	75	85	0.85
R4	SUS316	85	95	1.2
R4.5	SUS316	95	105	1.6
R5	SUS316	105	115	2.1
R5.5	SUS316	115	125	2.7
R6	SUS316	125	135	3.4
R6.5	SUS316	135	145	4.2
R7	SUS316	145	155	5.1
R7.5	SUS316	155	165	6.1
R8	SUS316	165	175	7.2
R8.5	SUS316	175	185	8.4
R9	SUS316	185	195	9.7
R9.5	SUS316	195	205	11.1
R10	SUS316	205	215	12.6
R10.5	SUS316	215	225	14.2
R11	SUS316	225	235	15.9
R11.5	SUS316	235	245	17.7
R12	SUS316	245	255	19.6
R12.5	SUS316	255	265	21.6
R13	SUS316	265	275	23.7
R13.5	SUS316	275	285	25.9
R14	SUS316	285	295	28.2
R14.5	SUS316	295	305	30.6
R15	SUS316	305	315	33.1
R15.5	SUS316	315	325	35.7
R16	SUS316	325	335	38.4
R16.5	SUS316	335	345	41.2
R17	SUS316	345	355	44.1
R17.5	SUS316	355	365	47.1
R18	SUS316	365	375	50.2
R18.5	SUS316	375	385	53.4
R19	SUS316	385	395	56.7
R19.5	SUS316	395	405	60.1
R20	SUS316	405	415	63.6
R20.5	SUS316	415	425	67.2
R21	SUS316	425	435	70.9
R21.5	SUS316	435	445	74.7
R22	SUS316	445	455	78.6
R22.5	SUS316	455	465	82.6
R23	SUS316	465	475	86.7
R23.5	SUS316	475	485	90.9
R24	SUS316	485	495	95.2
R24.5	SUS316	495	505	99.6
R25	SUS316	505	515	104.1
R25.5	SUS316	515	525	108.7
R26	SUS316	525	535	113.4
R26.5	SUS316	535	545	118.2
R27	SUS316	545	555	123.1
R27.5	SUS316	555	565	128.1
R28	SUS316	565	575	133.2
R28.5	SUS316	575	585	138.4
R29	SUS316	585	595	143.7
R29.5	SUS316	595	605	149.1
R30	SUS316	605	615	154.6
R30.5	SUS316	615	625	160.2
R31	SUS316	625	635	165.9
R31.5	SUS316	635	645	171.7
R32	SUS316	645	655	177.6
R32.5	SUS316	655	665	183.6
R33	SUS316	665	675	189.7
R33.5	SUS316	675	685	195.9
R34	SUS316	685	695	202.2
R34.5	SUS316	695	705	208.6
R35	SUS316	705	715	215.1
R35.5	SUS316	715	725	221.7
R36	SUS316	725	735	228.4
R36.5	SUS316	735	745	235.2
R37	SUS316	745	755	242.1
R37.5	SUS316	755	765	249.1
R38	SUS316	765	775	256.2
R38.5	SUS316	775	785	263.4
R39	SUS316	785	795	270.7
R39.5	SUS316	795	805	278.1
R40	SUS316	805	815	285.6
R40.5	SUS316	815	825	293.2
R41	SUS316	825	835	300.9
R41.5	SUS316	835	845	308.7
R42	SUS316	845	855	316.6
R42.5	SUS316	855	865	324.6
R43	SUS316	865	875	332.7
R43.5	SUS316	875	885	340.9
R44	SUS316	885	895	349.2
R44.5	SUS316	895	905	357.6
R45	SUS316	905	915	366.1
R45.5	SUS316	915	925	374.7
R46	SUS316	925	935	383.4
R46.5	SUS316	935	945	392.2
R47	SUS316	945	955	401.1
R47.5	SUS316	955	965	410.1
R48	SUS316	965	975	419.2
R48.5	SUS316	975	985	428.4
R49	SUS316	985	995	437.7
R49.5	SUS316	995	1005	447.1
R50	SUS316	1005	1015	456.6



STEP-1025

規格	材質	外径	長さ	重量
R1/4	SUS316	10	20	0.015
R1/2	SUS316	15	25	0.025
R3/4	SUS316	20	30	0.045
R1	SUS316	25	35	0.075
R1.5	SUS316	35	45	0.15
R2	SUS316	45	55	0.25
R2.5	SUS316	55	65	0.4
R3	SUS316	65	75	0.6
R3.5	SUS316	75	85	0.85
R4	SUS316	85	95	1.2
R4.5	SUS316	95	105	1.6
R5	SUS316	105	115	2.1
R5.5	SUS316	115	125	2.7
R6	SUS316	125	135	3.4
R6.5	SUS316	135	145	4.2
R7	SUS316	145	155	5.1
R7.5	SUS316	155	165	6.1
R8	SUS316	165	175	7.2
R8.5	SUS316	175	185	8.4
R9	SUS316	185	195	9.7
R9.5	SUS316	195	205	11.1
R10	SUS316	205	215	12.6
R10.5	SUS316	215	225	14.2
R11	SUS316	225	235	15.9
R11.5	SUS316	235	245	17.7
R12	SUS316	245	255	19.6
R12.5	SUS316	255	265	21.6
R13	SUS316	265	275	23.7
R13.5	SUS316	275	285	25.9
R14	SUS316	285	295	28.2
R14.5	SUS316	295	305	30.6
R15	SUS316	305	315	33.1
R15.5	SUS316	315	325	35.7
R16	SUS316	325	335	38.4
R16.5	SUS316	335	345	41.2
R17	SUS316	345	355	44.1
R17.5	SUS316	355	365	47.1
R18	SUS316	365	375	50.2
R18.5	SUS316	375	385	53.4
R19	SUS316	385	395	56.7
R19.5	SUS316	395	405	60.1
R20	SUS316	405	415	63.6
R20.5	SUS316	415	425	67.2
R21	SUS316	425	435	70.9
R21.5	SUS316	435	445	74.7
R22	SUS316	445	455	78.6
R22.5	SUS316	455	465	82.6
R23	SUS316	465	475	86.7
R23.5	SUS316	475	485	90.9
R24	SUS316	485	495	95.2
R24.5	SUS316	495	505	99.6
R25	SUS316	505	515	104.1
R25.5	SUS316	515	525	108.7
R26	SUS316	525	535	113.4
R26.5	SUS316	535	545	118.2
R27	SUS316	545	555	123.1
R27.5	SUS316	555	565	128.1
R28	SUS316	565	575	133.2
R28.5	SUS316	575	585	138.4
R29	SUS316	585	595	143.7
R29.5	SUS316	595	605	149.1
R30	SUS316	605	615	154.6
R30.5	SUS316	615	625	160.2
R31	SUS316	625	635	165.9
R31.5	SUS316	635	645	171.7
R32	SUS316	645	655	177.6
R32.5	SUS316	655	665	183.6
R33	SUS316	665	675	189.7
R33.5	SUS316	675	685	195.9
R34	SUS316	685	695	202.2
R34.5	SUS316	695	705	208.6
R35	SUS316	705	715	215.1
R35.5	SUS316	715	725	221.7
R36	SUS316	725	735	228.4
R36.5	SUS316	735	745	235.2
R37	SUS316	745	755	242.1
R37.5	SUS316	755	765	249.1
R38	SUS316	765	775	256.2
R38.5	SUS316	775	785	263.4
R39	SUS316	785	795	270.7
R39.5	SUS316	795	805	278.1
R40	SUS316	805	815	285.6
R40.5	SUS316	815	825	293.2
R41	SUS316	825	835	300.9
R41.5	SUS316	835	845	308.7
R42	SUS316	845	855	316.6
R42.5	SUS316	855	865	324.6
R43	SUS316	865	875	332.7
R43.5	SUS316	875	885	340.9
R44	SUS316	885	895	349.2
R44.5	SUS316	895	905	357.6
R45	SUS316	905	915	366.1
R45.5	SUS316	915	925	374.7
R46	SUS316	925	935	383.4
R46.5	SUS316	935	945	392.2
R47	SUS316	945	955	401.1
R47.5	SUS316	955	965	410.1
R48	SUS316	965	975	419.2
R48.5	SUS316	975	985	428.4
R49	SUS316	985	995	437.7
R49.5	SUS316	995	1005	447.1
R50	SUS316	1005	1015	456.6

仕様

メーカー	アオイ	型番	AWL-10-2
シリーズ	AW W-インターロック式締付継手	用途	エルボユニオン
適用パイプ	ステンレス鋼鋼管	適用パイプ外径	10mm
使用温度	-196~600℃	取付ねじ	R1/4"
推奨締付トルク	12~14N・m	材質	SUS316

高圧・高温・低温に耐えられます。

使用圧力はチューブ使用圧力に準拠する。

真空ラインでも使用可能です。

※プラスチックチューブ使用時は、インサートリングが別途必要となります。

RoHS対応