

品番 : EA425CN-123

品名 : G 3/8"x12mm ユニオン(圧力計/ステンレス製)



販売価格	2,700円(税抜) / 2,970円(税込)		
カタログ価格	2,700円(税抜) / 2,970円(税込)		
在庫数	最新在庫: 4 (2026/04/27 14:02現在)		
商品入数	1	販売単位	個
カタログページ	1024ページ		



規格	寸法	材質	重量
G1/2"	19	SUS316	13.15
G3/4"	21.5	SUS316	16.5
G1"	24	SUS316	20.5
G1.1/4"	26.5	SUS316	24.5
G1.1/2"	29	SUS316	28.5
G2"	31.5	SUS316	32.5
G2.1/2"	34	SUS316	36.5
G3"	36.5	SUS316	40.5
G3.1/2"	39	SUS316	44.5
G4"	41.5	SUS316	48.5
G4.1/2"	44	SUS316	52.5
G5"	46.5	SUS316	56.5
G5.1/2"	49	SUS316	60.5
G6"	51.5	SUS316	64.5
G6.1/2"	54	SUS316	68.5
G7"	56.5	SUS316	72.5
G7.1/2"	59	SUS316	76.5
G8"	61.5	SUS316	80.5
G8.1/2"	64	SUS316	84.5
G9"	66.5	SUS316	88.5
G9.1/2"	69	SUS316	92.5
G10"	71.5	SUS316	96.5
G10.1/2"	74	SUS316	100.5
G11"	76.5	SUS316	104.5
G11.1/2"	79	SUS316	108.5
G12"	81.5	SUS316	112.5
G12.1/2"	84	SUS316	116.5
G13"	86.5	SUS316	120.5
G13.1/2"	89	SUS316	124.5
G14"	91.5	SUS316	128.5
G14.1/2"	94	SUS316	132.5
G15"	96.5	SUS316	136.5
G15.1/2"	99	SUS316	140.5
G16"	101.5	SUS316	144.5
G16.1/2"	104	SUS316	148.5
G17"	106.5	SUS316	152.5
G17.1/2"	109	SUS316	156.5
G18"	111.5	SUS316	160.5
G18.1/2"	114	SUS316	164.5
G19"	116.5	SUS316	168.5
G19.1/2"	119	SUS316	172.5
G20"	121.5	SUS316	176.5
G20.1/2"	124	SUS316	180.5
G21"	126.5	SUS316	184.5
G21.1/2"	129	SUS316	188.5
G22"	131.5	SUS316	192.5
G22.1/2"	134	SUS316	196.5
G23"	136.5	SUS316	200.5
G23.1/2"	139	SUS316	204.5
G24"	141.5	SUS316	208.5
G24.1/2"	144	SUS316	212.5
G25"	146.5	SUS316	216.5
G25.1/2"	149	SUS316	220.5
G26"	151.5	SUS316	224.5
G26.1/2"	154	SUS316	228.5
G27"	156.5	SUS316	232.5
G27.1/2"	159	SUS316	236.5
G28"	161.5	SUS316	240.5
G28.1/2"	164	SUS316	244.5
G29"	166.5	SUS316	248.5
G29.1/2"	169	SUS316	252.5
G30"	171.5	SUS316	256.5
G30.1/2"	174	SUS316	260.5
G31"	176.5	SUS316	264.5
G31.1/2"	179	SUS316	268.5
G32"	181.5	SUS316	272.5
G32.1/2"	184	SUS316	276.5
G33"	186.5	SUS316	280.5
G33.1/2"	189	SUS316	284.5
G34"	191.5	SUS316	288.5
G34.1/2"	194	SUS316	292.5
G35"	196.5	SUS316	296.5
G35.1/2"	199	SUS316	300.5
G36"	201.5	SUS316	304.5
G36.1/2"	204	SUS316	308.5
G37"	206.5	SUS316	312.5
G37.1/2"	209	SUS316	316.5
G38"	211.5	SUS316	320.5
G38.1/2"	214	SUS316	324.5
G39"	216.5	SUS316	328.5
G39.1/2"	219	SUS316	332.5
G40"	221.5	SUS316	336.5
G40.1/2"	224	SUS316	340.5
G41"	226.5	SUS316	344.5
G41.1/2"	229	SUS316	348.5
G42"	231.5	SUS316	352.5
G42.1/2"	234	SUS316	356.5
G43"	236.5	SUS316	360.5
G43.1/2"	239	SUS316	364.5
G44"	241.5	SUS316	368.5
G44.1/2"	244	SUS316	372.5
G45"	246.5	SUS316	376.5
G45.1/2"	249	SUS316	380.5
G46"	251.5	SUS316	384.5
G46.1/2"	254	SUS316	388.5
G47"	256.5	SUS316	392.5
G47.1/2"	259	SUS316	396.5
G48"	261.5	SUS316	400.5
G48.1/2"	264	SUS316	404.5
G49"	266.5	SUS316	408.5
G49.1/2"	269	SUS316	412.5
G50"	271.5	SUS316	416.5
G50.1/2"	274	SUS316	420.5
G51"	276.5	SUS316	424.5
G51.1/2"	279	SUS316	428.5
G52"	281.5	SUS316	432.5
G52.1/2"	284	SUS316	436.5
G53"	286.5	SUS316	440.5
G53.1/2"	289	SUS316	444.5
G54"	291.5	SUS316	448.5
G54.1/2"	294	SUS316	452.5
G55"	296.5	SUS316	456.5
G55.1/2"	299	SUS316	460.5
G56"	301.5	SUS316	464.5
G56.1/2"	304	SUS316	468.5
G57"	306.5	SUS316	472.5
G57.1/2"	309	SUS316	476.5
G58"	311.5	SUS316	480.5
G58.1/2"	314	SUS316	484.5
G59"	316.5	SUS316	488.5
G59.1/2"	319	SUS316	492.5
G60"	321.5	SUS316	496.5
G60.1/2"	324	SUS316	500.5
G61"	326.5	SUS316	504.5
G61.1/2"	329	SUS316	508.5
G62"	331.5	SUS316	512.5
G62.1/2"	334	SUS316	516.5
G63"	336.5	SUS316	520.5
G63.1/2"	339	SUS316	524.5
G64"	341.5	SUS316	528.5
G64.1/2"	344	SUS316	532.5
G65"	346.5	SUS316	536.5
G65.1/2"	349	SUS316	540.5
G66"	351.5	SUS316	544.5
G66.1/2"	354	SUS316	548.5
G67"	356.5	SUS316	552.5
G67.1/2"	359	SUS316	556.5
G68"	361.5	SUS316	560.5
G68.1/2"	364	SUS316	564.5
G69"	366.5	SUS316	568.5
G69.1/2"	369	SUS316	572.5
G70"	371.5	SUS316	576.5
G70.1/2"	374	SUS316	580.5
G71"	376.5	SUS316	584.5
G71.1/2"	379	SUS316	588.5
G72"	381.5	SUS316	592.5
G72.1/2"	384	SUS316	596.5
G73"	386.5	SUS316	600.5
G73.1/2"	389	SUS316	604.5
G74"	391.5	SUS316	608.5
G74.1/2"	394	SUS316	612.5
G75"	396.5	SUS316	616.5
G75.1/2"	399	SUS316	620.5
G76"	401.5	SUS316	624.5
G76.1/2"	404	SUS316	628.5
G77"	406.5	SUS316	632.5
G77.1/2"	409	SUS316	636.5
G78"	411.5	SUS316	640.5
G78.1/2"	414	SUS316	644.5
G79"	416.5	SUS316	648.5
G79.1/2"	419	SUS316	652.5
G80"	421.5	SUS316	656.5
G80.1/2"	424	SUS316	660.5
G81"	426.5	SUS316	664.5
G81.1/2"	429	SUS316	668.5
G82"	431.5	SUS316	672.5
G82.1/2"	434	SUS316	676.5
G83"	436.5	SUS316	680.5
G83.1/2"	439	SUS316	684.5
G84"	441.5	SUS316	688.5
G84.1/2"	444	SUS316	692.5
G85"	446.5	SUS316	696.5
G85.1/2"	449	SUS316	700.5
G86"	451.5	SUS316	704.5
G86.1/2"	454	SUS316	708.5
G87"	456.5	SUS316	712.5
G87.1/2"	459	SUS316	716.5
G88"	461.5	SUS316	720.5
G88.1/2"	464	SUS316	724.5
G89"	466.5	SUS316	728.5
G89.1/2"	469	SUS316	732.5
G90"	471.5	SUS316	736.5
G90.1/2"	474	SUS316	740.5
G91"	476.5	SUS316	744.5
G91.1/2"	479	SUS316	748.5
G92"	481.5	SUS316	752.5
G92.1/2"	484	SUS316	756.5
G93"	486.5	SUS316	760.5
G93.1/2"	489	SUS316	764.5
G94"	491.5	SUS316	768.5
G94.1/2"	494	SUS316	772.5
G95"	496.5	SUS316	776.5
G95.1/2"	499	SUS316	780.5
G96"	501.5	SUS316	784.5
G96.1/2"	504	SUS316	788.5
G97"	506.5	SUS316	792.5
G97.1/2"	509	SUS316	796.5
G98"	511.5	SUS316	800.5
G98.1/2"	514	SUS316	804.5
G99"	516.5	SUS316	808.5
G99.1/2"	519	SUS316	812.5
G100"	521.5	SUS316	816.5
G100.1/2"	524	SUS316	820.5

仕様

メーカー	アオイ	型番	AWP-12-3
シリーズ	AW W-インターロック式締付継手	用途	圧力計ユニオン
適用パイプ	ステンレス鋼鋼管	適用パイプ外径	12mm
使用温度	-196~600℃	取付ねじ	G3/8"
推奨締付トルク	22~24N・m	材質	SUS316

高圧・高温・低温に耐えられます。

使用圧力はチューブ使用圧力に準拠する。

真空ラインでも使用可能です。

※プラスチックチューブ使用時は、インサートリングが別途必要となります。

RoHS対応品

株式会社エスコ

大阪府大阪市西区立売堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.