

品番 : EA538CF-1

品名：0.5 - 6.0mm<sup>2</sup> 壓着ペンチ(絶縁端子用)



販売価格	5,340円(税抜)／5,874円(税込)		
カタログ価格	5,340円(税抜)／5,874円(税込)		
在庫数	最新在庫: 17 (2026/02/02 04:20現在)		
商品入数	1	販売単位	個
カタログページ	0249ページ		



A. In-Crop Management						
A.L.C.	GR.	BR.	WT.	CH.	WT.	AMOUNT
4/15	21300	15300	10.00	15	1200	0.01%
4/16	18000	10500	10.00	28	1400	0.01%
4/17	15000	10500	10.00	30	1500	0.01%
4/18	10000	5200	3.24	22	6400	0.06%
4/19	8300	5200	3.24	23	5800	0.05%
4/20	7000	5200	3.24	24	5600	0.05%
4/21	5200	5200	3.24	25	3500	0.04%
4/22	4700	5200	3.24	26	2640	0.03%
4/23	4200	5200	3.24	27	2000	0.02%
4/24	3200	5200	3.24	28	1900	0.02%
4/25	2800	5200	3.24	29	1800	0.02%
4/26	2400	5200	3.24	30	1800	0.02%
4/27	2000	5200	3.24	31	1800	0.02%
4/28	1800	5200	3.24	32	1800	0.02%
4/29	1600	5200	3.24	33	1800	0.02%
4/30	1400	5200	3.24	34	20	0.00%
5/1	1000	5200	3.24	35	20	0.00%
5/2	800	5200	3.24	36	20	0.00%
5/3	600	5200	3.24	37	20	0.00%
5/4	400	5200	3.24	38	20	0.00%
5/5	200	5200	3.24	39	20	0.00%
5/6	100	5200	3.24	40	20	0.00%
5/7	50	5200	3.24	41	20	0.00%
5/8	20	5200	3.24	42	20	0.00%
5/9	10	5200	3.24	43	20	0.00%
5/10	5	5200	3.24	44	20	0.00%
5/11	2	5200	3.24	45	20	0.00%
5/12	1	5200	3.24	46	20	0.00%
5/13	0.5	5200	3.24	47	20	0.00%
5/14	0.25	5200	3.24	48	20	0.00%
5/15	0.125	5200	3.24	49	20	0.00%
5/16	0.0625	5200	3.24	50	20	0.00%
5/17	0.03125	5200	3.24	51	20	0.00%
5/18	0.015625	5200	3.24	52	20	0.00%
5/19	0.0078125	5200	3.24	53	20	0.00%
5/20	0.00390625	5200	3.24	54	20	0.00%
5/21	0.001953125	5200	3.24	55	20	0.00%
5/22	0.0009765625	5200	3.24	56	20	0.00%
5/23	0.00048828125	5200	3.24	57	20	0.00%
5/24	0.000244140625	5200	3.24	58	20	0.00%
5/25	0.0001220703125	5200	3.24	59	20	0.00%
5/26	0.00006103515625	5200	3.24	60	20	0.00%
5/27	0.000030517578125	5200	3.24	61	20	0.00%
5/28	0.0000152587890625	5200	3.24	62	20	0.00%
5/29	0.00000762939453125	5200	3.24	63	20	0.00%
5/30	0.000003814697265625	5200	3.24	64	20	0.00%
5/31	0.0000019073486328125	5200	3.24	65	20	0.00%
5/32	0.00000095367431640625	5200	3.24	66	20	0.00%
5/33	0.000000476837158203125	5200	3.24	67	20	0.00%
5/34	0.0000002384185791015625	5200	3.24	68	20	0.00%
5/35	0.00000012020928955078125	5200	3.24	69	20	0.00%
5/36	0.000000060104644775390625	5200	3.24	70	20	0.00%
5/37	0.0000000300523223876953125	5200	3.24	71	20	0.00%
5/38	0.00000001502616119384765625	5200	3.24	72	20	0.00%
5/39	0.000000007513080596923828125	5200	3.24	73	20	0.00%
5/40	0.0000000037565402984619140625	5200	3.24	74	20	0.00%
5/41	0.00000000187827014923095703125	5200	3.24	75	20	0.00%
5/42	0.000000000939135074615478515625	5200	3.24	76	20	0.00%
5/43	0.0000000004695675373077892578125	5200	3.24	77	20	0.00%
5/44	0.00000000023478376865389462890625	5200	3.24	78	20	0.00%
5/45	0.000000000117391884326947314453125	5200	3.24	79	20	0.00%
5/46	0.0000000000586959421634736572265625	5200	3.24	80	20	0.00%
5/47	0.000000000029347971081736828613125	5200	3.24	81	20	0.00%
5/48	0.00000000001467398554086841435625	5200	3.24	82	20	0.00%
5/49	0.000000000007336992770434207278125	5200	3.24	83	20	0.00%
5/50	0.0000000000036684963852171033890625	5200	3.24	84	20	0.00%
5/51	0.00000000000183424819260855169453125	5200	3.24	85	20	0.00%
5/52	0.0000000000009171240963042758472265625	5200	3.24	86	20	0.00%
5/53	0.000000000000458562048152137923613125	5200	3.24	87	20	0.00%
5/54	0.00000000000022928102407606896185625	5200	3.24	88	20	0.00%
5/55	0.0000000000001146405120380344809278125	5200	3.24	89	20	0.00%
5/56	0.000000000000057320256019017240463625	5200	3.24	90	20	0.00%
5/57	0.0000000000000286601280095086202313125	5200	3.24	91	20	0.00%
5/58	0.00000000000001433006400475431015625	5200	3.24	92	20	0.00%
5/59	0.00000000000000716503200237775078125	5200	3.24	93	20	0.00%
5/60	0.000000000000003582516001188875390625	5200	3.24	94	20	0.00%
5/61	0.0000000000000017912580005944376953125	5200	3.24	95	20	0.00%
5/62	0.0000000000000008956290002972218972265625	5200	3.24	96	20	0.00%
5/63	0.000000000000000447814500148611098613125	5200	3.24	97	20	0.00%
5/64	0.000000000000000223907250074305549313625	5200	3.24	98	20	0.00%
5/65	0.000000000000000111953625037152774658125	5200	3.24	99	20	0.00%
5/66	0.0000000000000000559768125185763873290625	5200	3.24	100	20	0.00%
5/67	0.00000000000000002798840625928819364453125	5200	3.24	101	20	0.00%
5/68	0.000000000000000013994203124644096822313125	5200	3.24	102	20	0.00%
5/69	0.00000000000000000699710156232204841115625	5200	3.24	103	20	0.00%
5/70	0.00000000000000000349855078166102205578125	5200	3.24	104	20	0.00%
5/71	0.000000000000000001749275390830511027890625	5200	3.24	105	20	0.00%
5/72	0.0000000000000000008746376954152555539453125	5200	3.24	106	20	0.00%
5/73	0.00000000000000000043731884770762777697265625	5200	3.24	107	20	0.00%
5/74	0.000000000000000000218659423853813888488125	5200	3.24	108	20	0.00%
5/75	0.00000000000000000010932971192690694424453125	5200	3.24	109	20	0.00%
5/76	0.000000000000000000054664855963453472122313125	5200	3.24	110	20	0.00%
5/77	0.00000000000000000002733242798172673606115625	5200	3.24	111	20	0.00%
5/78	0.00000000000000000001366621399086336803055625	5200	3.24	112	20	0.00%
5/79	0.00000000000000000000683310699953168015278125	5200	3.24	113	20	0.00%
5/80	0.000000000000000000003416553499765840073390625	5200	3.24	114	20	0.00%
5/81	0.0000000000000000000017082767498829200366953125	5200	3.24	115	20	0.00%
5/82	0.00000000000000000000085413837494146001834453125	5200	3.24	116	20	0.00%
5/83	0.000000000000000000000427069187470730009172313125	5200	3.24	117	20	0.00%
5/84	0.00000000000000000000021353459373536500458615625	5200	3.24	118	20	0.00%
5/85	0.000000000000000000000106767296867682502293055625	5200	3.24	119	20	0.00%
5/86	0.0000000000000000000000533836484338341251465278125	5200	3.24	120	20	0.00%
5/87	0.0000000000000000000000266918242169170625732638125	5200	3.24	121	20	0.00%
5/88	0.0000000000000000000000133459121084585312501318125	5200	3.24	122	20	0.00%
5/89	0.000000000000000000000006672956054229265625006593125	5200	3.24	123	20	0.00%
5/90	0.00000000000000000000000333647802711463253125318125	5200	3.24	124	20	0.00%
5/91	0.00000000000000000000000166823901355731625156593125	5200	3.24	125	20	0.00%
5/92	0.0000000000000000000000008341195067786581250779653125	5200	3.24	126	20	0.00%
5/93	0.00000000000000000000000041705975338932912538978125	5200	3.24	127	20	0.00%
5/94	0.000000000000000000000000208529876694644562519493125	5200	3.24	128	20	0.00%
5/95	0.00000000000000000000000010426493834732228125974653125	5200	3.24	129	20	0.00%
5/96	0.000000000000000000000000052132469173661141254873125	5200	3.24	130	20	0.00%
5/97	0.00000000000000000000000002606623458783557062523653125	5200	3.24	131	20	0.00%
5/98	0.0000000000000000000000000130331172939177853125118125	5200	3.24	132	20	0.00%
5/99	0.000000000000000000000000006516558646958892625590653125	5200	3.24	133	20	0.00%
5/100	0.00000000000000000000000000325827932347944631252953125	5200	3.24	134	20	0.00%
5/101	0.000000000000000000000000001629139661739723125147653125	5200	3.24	135	20	0.00%
5/102	0.0000000000000000000000000008145698308698615625738125	5200	3.24	136	20	0.00%
5/103	0.00000000000000000000000000040728491543493078125368125	5200	3.24	137	20	0.00%
5/104	0.0000000000000000000000000002036424577174653937518125	5200	3.24	138	20	0.00%
5/105	0.00000000000000000000000000010182122885873269687593125	5200	3.24	139	20	0.00%
5/106	0.0000000000000000000000000000509106144293663484379653125	5200	3.24	140	20	0.00%
5/107	0.00000000000000000000000000002545530721468317421898125	5200	3.24	141	20	0.00%
5/108	0.000000000000000000000000000012727653607341587109493125	5200	3.24	142	20	0.00%
5/109	0.00000000000000000000000000000636382680367059355474653125	5200	3.24	143	20	0.00%
5/110	0.0000000000000000000000000000031819134018352967773738125	5200	3.24	144	20	0.00%
5/111	0.0000000000000000000000000000015909567009176488886868125	5200	3.24	145	20	0.00%
5/112	0.0000000000000000000000000000007954783504588244443434653125	5200	3.24	146	20	0.00%
5/113	0.000000000000000000000000000000397739175229412222171738125	5200	3.24	147	20	0.00%
5/114	0.000000000000000000000000000000198869587614706111085868125	5200	3.24	148	20	0.00%
5/115	0.000000000000000000000000000000099434993805353055542938125	5200	3.24	149	20	0.00%
5/116	0.0000000000000000000000000000000497174969026765277746938125	5200	3.24	150	2	

ロック機能付き。ハンドルの握り込みでロックのオンオフを切り替えます。

仕様

全長(mm)	260	重量(g)	600
圧着範囲(mm)	0.5-1.5・2.5 4.0-6.0	材質	鉄、樹脂
サイズ(W×D×H)mm	260x105x20		

絶縁端子用

ラチェット式

ハンドルの握り込みでロックのオンオフを切り替えます

### 途中解除レバー付き

### 樹脂ハンドル

株式会社エスコ

大阪府大阪市西区立堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.