

品番：EA829DB-20D

品名：M20 x 1 ハンドタップ(SKS2/仕上)



販売価格	7,740円(税抜) / 8,514円(税込)		
カタログ価格	7,740円(税抜) / 8,514円(税込)		
在庫数	最新在庫: 1 (2026/04/03 06:31現在)		
商品入数	1	販売単位	本
カタログページ	0902ページ		



再処理材	構造用鋼 (S45C)	炭素工具鋼 (SK5)	合金工具鋼 (SKS2)	ステンレス鋼 (SUS304)
○	○	○	○	△



呼び径の長さについて
● 標準品は、下記表にて
● 異なる長さの標準品は
● 異なる呼び径の標準品は
● 異なる呼び径の標準品は
● 異なる呼び径の標準品は

呼び径	標準品長さ	標準品長さ	標準品長さ
M2.0	10	12	15
M2.5	12	15	20
M3.0	15	20	25
M3.5	20	25	30
M4.0	25	30	35
M4.5	30	35	40
M5.0	35	40	45
M5.5	40	45	50
M6.0	45	50	55
M6.5	50	55	60
M7.0	55	60	65
M7.5	60	65	70
M8.0	65	70	75
M8.5	70	75	80
M9.0	75	80	85
M9.5	80	85	90
M10.0	85	90	95
M10.5	90	95	100
M11.0	95	100	105
M11.5	100	105	110
M12.0	105	110	115
M12.5	110	115	120
M13.0	115	120	125
M13.5	120	125	130
M14.0	125	130	135
M14.5	130	135	140
M15.0	135	140	145
M15.5	140	145	150
M16.0	145	150	155
M16.5	150	155	160
M17.0	155	160	165
M17.5	160	165	170
M18.0	165	170	175
M18.5	170	175	180
M19.0	175	180	185
M19.5	180	185	190
M20.0	185	190	195
M20.5	190	195	200
M21.0	195	200	205
M21.5	200	205	210
M22.0	205	210	215
M22.5	210	215	220
M23.0	215	220	225
M23.5	220	225	230
M24.0	225	230	235
M24.5	230	235	240
M25.0	235	240	245
M25.5	240	245	250
M26.0	245	250	255
M26.5	250	255	260
M27.0	255	260	265
M27.5	260	265	270
M28.0	265	270	275
M28.5	270	275	280
M29.0	275	280	285
M29.5	280	285	290
M30.0	285	290	295
M30.5	290	295	300
M31.0	295	300	305
M31.5	300	305	310
M32.0	305	310	315
M32.5	310	315	320
M33.0	315	320	325
M33.5	320	325	330
M34.0	325	330	335
M34.5	330	335	340
M35.0	335	340	345
M35.5	340	345	350
M36.0	345	350	355
M36.5	350	355	360
M37.0	355	360	365
M37.5	360	365	370
M38.0	365	370	375
M38.5	370	375	380
M39.0	375	380	385
M39.5	380	385	390
M40.0	385	390	395
M40.5	390	395	400
M41.0	395	400	405
M41.5	400	405	410
M42.0	405	410	415
M42.5	410	415	420
M43.0	415	420	425
M43.5	420	425	430
M44.0	425	430	435
M44.5	430	435	440
M45.0	435	440	445
M45.5	440	445	450
M46.0	445	450	455
M46.5	450	455	460
M47.0	455	460	465
M47.5	460	465	470
M48.0	465	470	475
M48.5	470	475	480
M49.0	475	480	485
M49.5	480	485	490
M50.0	485	490	495
M50.5	490	495	500
M51.0	495	500	505
M51.5	500	505	510
M52.0	505	510	515
M52.5	510	515	520
M53.0	515	520	525
M53.5	520	525	530
M54.0	525	530	535
M54.5	530	535	540
M55.0	535	540	545
M55.5	540	545	550
M56.0	545	550	555
M56.5	550	555	560
M57.0	555	560	565
M57.5	560	565	570
M58.0	565	570	575
M58.5	570	575	580
M59.0	575	580	585
M59.5	580	585	590
M60.0	585	590	595
M60.5	590	595	600
M61.0	595	600	605
M61.5	600	605	610
M62.0	605	610	615
M62.5	610	615	620
M63.0	615	620	625
M63.5	620	625	630
M64.0	625	630	635
M64.5	630	635	640
M65.0	635	640	645
M65.5	640	645	650
M66.0	645	650	655
M66.5	650	655	660
M67.0	655	660	665
M67.5	660	665	670
M68.0	665	670	675
M68.5	670	675	680
M69.0	675	680	685
M69.5	680	685	690
M70.0	685	690	695
M70.5	690	695	700
M71.0	695	700	705
M71.5	700	705	710
M72.0	705	710	715
M72.5	710	715	720
M73.0	715	720	725
M73.5	720	725	730
M74.0	725	730	735
M74.5	730	735	740
M75.0	735	740	745
M75.5	740	745	750
M76.0	745	750	755
M76.5	750	755	760
M77.0	755	760	765
M77.5	760	765	770
M78.0	765	770	775
M78.5	770	775	780
M79.0	775	780	785
M79.5	780	785	790
M80.0	785	790	795
M80.5	790	795	800
M81.0	795	800	805
M81.5	800	805	810
M82.0	805	810	815
M82.5	810	815	820
M83.0	815	820	825
M83.5	820	825	830
M84.0	825	830	835
M84.5	830	835	840
M85.0	835	840	845
M85.5	840	845	850
M86.0	845	850	855
M86.5	850	855	860
M87.0	855	860	865
M87.5	860	865	870
M88.0	865	870	875
M88.5	870	875	880
M89.0	875	880	885
M89.5	880	885	890
M90.0	885	890	895
M90.5	890	895	900
M91.0	895	900	905
M91.5	900	905	910
M92.0	905	910	915
M92.5	910	915	920
M93.0	915	920	925
M93.5	920	925	930
M94.0	925	930	935
M94.5	930	935	940
M95.0	935	940	945
M95.5	940	945	950
M96.0	945	950	955
M96.5	950	955	960
M97.0	955	960	965
M97.5	960	965	970
M98.0	965	970	975
M98.5	970	975	980
M99.0	975	980	985
M99.5	980	985	990
M100.0	985	990	995

仕様

メーカー	イシハシ精工	呼び	M20×1.0
全長	80mm	■巾	12mm
材質	SKS_2	対応被削材	構造用鋼、低炭素鋼、鋳鉄、アルミニウム合金、銅合金
JISIII級			
仕上タップ(喰付1.5P)			
SKS2(JIS)とは、合金工具鋼を意味し、炭素工具鋼にクロム、タングステン、モリブデン等金属成分を添加し、焼入れ硬さ、じん性、耐摩耗性を増した鋼の一種です。			

株式会社エスコ

大阪府大阪市西区立売堀3丁目8番14号 06-6532-6226(代表)

© 2018 ESCO Co.,Ltd.