

品番：EA829SE-14B

品名：M14x1.5 スパ イラトップ° (ステンレス用・ホモ処理)



販売価格	5,120円(税抜) / 5,632円(税込)		
カタログ価格	5,120円(税抜) / 5,632円(税込)		
在庫数	最新在庫: 1 (2026/06/26 03:10現在)		
商品入数	1	販売単位	本
カタログページ	0898ページ		



型番	外径	全長	首下長	シャンク径	溝数
EA829SE-14B	14	88	48	10.5	3
EA829SE-16B	16	100	60	12.5	3
EA829SE-18B	18	112	72	14.5	3
EA829SE-20B	20	124	84	16.5	3
EA829SE-22B	22	136	96	18.5	3
EA829SE-24B	24	148	108	20.5	3
EA829SE-26B	26	160	120	22.5	3
EA829SE-28B	28	172	132	24.5	3
EA829SE-30B	30	184	144	26.5	3
EA829SE-32B	32	196	156	28.5	3
EA829SE-34B	34	208	168	30.5	3
EA829SE-36B	36	220	180	32.5	3
EA829SE-38B	38	232	192	34.5	3
EA829SE-40B	40	244	204	36.5	3
EA829SE-42B	42	256	216	38.5	3
EA829SE-44B	44	268	228	40.5	3
EA829SE-46B	46	280	240	42.5	3
EA829SE-48B	48	292	252	44.5	3
EA829SE-50B	50	304	264	46.5	3
EA829SE-52B	52	316	276	48.5	3
EA829SE-54B	54	328	288	50.5	3
EA829SE-56B	56	340	300	52.5	3
EA829SE-58B	58	352	312	54.5	3
EA829SE-60B	60	364	324	56.5	3
EA829SE-62B	62	376	336	58.5	3
EA829SE-64B	64	388	348	60.5	3
EA829SE-66B	66	400	360	62.5	3
EA829SE-68B	68	412	372	64.5	3
EA829SE-70B	70	424	384	66.5	3
EA829SE-72B	72	436	396	68.5	3
EA829SE-74B	74	448	408	70.5	3
EA829SE-76B	76	460	420	72.5	3
EA829SE-78B	78	472	432	74.5	3
EA829SE-80B	80	484	444	76.5	3
EA829SE-82B	82	496	456	78.5	3
EA829SE-84B	84	508	468	80.5	3
EA829SE-86B	86	520	480	82.5	3
EA829SE-88B	88	532	492	84.5	3
EA829SE-90B	90	544	504	86.5	3
EA829SE-92B	92	556	516	88.5	3
EA829SE-94B	94	568	528	90.5	3
EA829SE-96B	96	580	540	92.5	3
EA829SE-98B	98	592	552	94.5	3
EA829SE-100B	100	604	564	96.5	3

呼び	外径	全長	首下長	シャンク径	溝数
2.5P	14	88	48	10.5	3
2.5P	16	100	60	12.5	3
2.5P	18	112	72	14.5	3
2.5P	20	124	84	16.5	3
2.5P	22	136	96	18.5	3
2.5P	24	148	108	20.5	3
2.5P	26	160	120	22.5	3
2.5P	28	172	132	24.5	3
2.5P	30	184	144	26.5	3
2.5P	32	196	156	28.5	3
2.5P	34	208	168	30.5	3
2.5P	36	220	180	32.5	3
2.5P	38	232	192	34.5	3
2.5P	40	244	204	36.5	3
2.5P	42	256	216	38.5	3
2.5P	44	268	228	40.5	3
2.5P	46	280	240	42.5	3
2.5P	48	292	252	44.5	3
2.5P	50	304	264	46.5	3
2.5P	52	316	276	48.5	3
2.5P	54	328	288	50.5	3
2.5P	56	340	300	52.5	3
2.5P	58	352	312	54.5	3
2.5P	60	364	324	56.5	3
2.5P	62	376	336	58.5	3
2.5P	64	388	348	60.5	3
2.5P	66	400	360	62.5	3
2.5P	68	412	372	64.5	3
2.5P	70	424	384	66.5	3
2.5P	72	436	396	68.5	3
2.5P	74	448	408	70.5	3
2.5P	76	460	420	72.5	3
2.5P	78	472	432	74.5	3
2.5P	80	484	444	76.5	3
2.5P	82	496	456	78.5	3
2.5P	84	508	468	80.5	3
2.5P	86	520	480	82.5	3
2.5P	88	532	492	84.5	3
2.5P	90	544	504	86.5	3
2.5P	92	556	516	88.5	3
2.5P	94	568	528	90.5	3
2.5P	96	580	540	92.5	3
2.5P	98	592	552	94.5	3
2.5P	100	604	564	96.5	3

呼び	外径	全長	首下長	シャンク径	溝数
2.5P	14	88	48	10.5	3
2.5P	16	100	60	12.5	3
2.5P	18	112	72	14.5	3
2.5P	20	124	84	16.5	3
2.5P	22	136	96	18.5	3
2.5P	24	148	108	20.5	3
2.5P	26	160	120	22.5	3
2.5P	28	172	132	24.5	3
2.5P	30	184	144	26.5	3
2.5P	32	196	156	28.5	3
2.5P	34	208	168	30.5	3
2.5P	36	220	180	32.5	3
2.5P	38	232	192	34.5	3
2.5P	40	244	204	36.5	3
2.5P	42	256	216	38.5	3
2.5P	44	268	228	40.5	3
2.5P	46	280	240	42.5	3
2.5P	48	292	252	44.5	3
2.5P	50	304	264	46.5	3
2.5P	52	316	276	48.5	3
2.5P	54	328	288	50.5	3
2.5P	56	340	300	52.5	3
2.5P	58	352	312	54.5	3
2.5P	60	364	324	56.5	3
2.5P	62	376	336	58.5	3
2.5P	64	388	348	60.5	3
2.5P	66	400	360	62.5	3
2.5P	68	412	372	64.5	3
2.5P	70	424	384	66.5	3
2.5P	72	436	396	68.5	3
2.5P	74	448	408	70.5	3
2.5P	76	460	420	72.5	3
2.5P	78	472	432	74.5	3
2.5P	80	484	444	76.5	3
2.5P	82	496	456	78.5	3
2.5P	84	508	468	80.5	3
2.5P	86	520	480	82.5	3
2.5P	88	532	492	84.5	3
2.5P	90	544	504	86.5	3
2.5P	92	556	516	88.5	3
2.5P	94	568	528	90.5	3
2.5P	96	580	540	92.5	3
2.5P	98	592	552	94.5	3
2.5P	100	604	564	96.5	3

呼び	外径	全長	首下長	シャンク径	溝数
2.5P	14	88	48	10.5	3
2.5P	16	100	60	12.5	3
2.5P	18	112	72	14.5	3
2.5P	20	124	84	16.5	3
2.5P	22	136	96	18.5	3
2.5P	24	148	108	20.5	3
2.5P	26	160	120	22.5	3
2.5P	28	172	132	24.5	3
2.5P	30	184	144	26.5	3
2.5P	32	196	156	28.5	3
2.5P	34	208	168	30.5	3
2.5P	36	220	180	32.5	3
2.5P	38	232	192	34.5	3
2.5P	40	244	204	36.5	3
2.5P	42	256	216	38.5	3
2.5P	44	268	228	40.5	3
2.5P	46	280	240	42.5	3
2.5P	48	292	252	44.5	3
2.5P	50	304	264	46.5	3
2.5P	52	316	276	48.5	3
2.5P	54	328	288	50.5	3
2.5P	56	340	300	52.5	3
2.5P	58	352	312	54.5	3
2.5P	60	364	324	56.5	3
2.5P	62	376	336	58.5	3
2.5P	64	388	348	60.5	3
2.5P	66	400	360	62.5	3
2.5P	68	412	372	64.5	3
2.5P	70	424	384	66.5	3
2.5P	72	436	396	68.5	3
2.5P	74	448	408	70.5	3
2.5P	76	460	420	72.5	3
2.5P	78	472	432	74.5	3
2.5P	80	484	444	76.5	3
2.5P	82	496	456	78.5	3
2.5P	84	508	468	80.5	3
2.5P	86	520	480	82.5	3
2.5P	88	532	492	84.5	3
2.5P	90	544	504	86.5	3
2.5P	92	556	516	88.5	3
2.5P	94	568	528	90.5	3
2.5P	96	580	540	92.5	3
2.5P	98	592	552	94.5	3
2.5P	100	604	564	96.5	3

呼び	外径	全長	首下長	シャンク径	溝数
2.5P	14	88	48	10.5	3
2.5P	16	100	60	12.5	3
2.5P	18	112	72	14.5	3
2.5P	20	124	84	16.5	3
2.5P	22	136	96	18.5	3
2.5P	24	148	108	20.5	3
2.5P	26	160	120	22.5	3
2.5P	28	172	132	24.5	3
2.5P	30	184	144	26.5	3
2.5P	32	196	156	28.5	3
2.5P	34	208	168	30.5	3
2.5P	36	220	180	32.5	3
2.5P	38	232	192	34.5	3
2.5P	40	244	204	36.5	3
2.5P	42	256	216	38.5	3
2.5P	44	268	228	40.5	3
2.5P	46	280	240	42.5	3
2.5P	48	292	252	44.5	3
2.5P	50	304	264	46.5	3
2.5P	52	316	276	48.5	3
2.5P	54	328	288	50.5	3
2.5P	56	340	300	52.5	3
2.5P	58	352	312	54.5	3
2.5P	60	364	324	56.5	3
2.5P	62	376	336	58.5	3
2.5P	64	388	348	60.5	3
2.5P	66	400	360	62.5	3
2.5P	68	412	372	64.5	3
2.5P	70	424	384	66.5	3
2.5P	72	436	396	68.5	3
2.5P	74	448	408	70.5	3
2.5P	76	460	420	72.5	3
2.5P	78	472	432	74.5	3
2.5P	80	484	444	76.5	3
2.5P	82	496	456	78.5	3
2.5P	84	508	468	80.5	3
2.5P	86	520	480	82.5	3
2.5P	88	532	492	84.5	3