

品番：EA949DV-602

品名：M 6x 12mm強力六角ボルト(SUS/ナットワッシャ付全ねじ)



販売価格	595円(税抜)／ 655円(税込)			
カタログ価格	595円(税抜)／655円(税込)			
在庫数	最新在庫: 10 （2026/02/18 22:24現在）			
商品入数	1	販売単位	ST	
カタログページ	1247ページ			



◆Bumax 六角ボルト
●製品規格 ISO 4014/ISO 19181
●材質 A4-80 (SUS316, HiMo)
●ねじ規格 ISO 2010 (JIS B 1180, JIS B 1181)
●強度クラス Class 8.8
●材質指定 SUS316/HiMo
●ねじ径 M6
●ねじ長さ 12mm
●全ねじ
●全ねじ長さ 12mm

機械的特性比較		材料	強度	耐力
材料	規格	強度	耐力	耐力
A2-50	ISO 4014	500	210	21.4
A4-70	ISO 4014	700	210	21.4
A4-80	ISO 4014	800	210	21.4
SUS316/HiMo	ISO 4014	800	210	21.4

◆化学成分比較・試験値表のチャート						
※単位: 質量パーセント (質量%)						
材料名	C	Si	Mn	P	S	その他
6060-T6	0.50	1.75	0.13	0.010	0.010	—
6061-T6	0.58	1.6-1.8	0.14	0.010	0.010	—
6063-T5	0.52	1.6-1.8	0.14	0.010	0.010	—
6061-T6	0.55	1.6-1.8	0.14	0.010	0.010	—

強度クラスの比較		強度	耐力
強度	耐力	強度	耐力
A2-70 (SUS304)	1.400	A2-70 (SUS304)	1.400
A2-80 (SUS304)	1.800	A2-80 (SUS304)	1.800
A4-80 (SUS316)	1.012	A4-80 (SUS316)	1.012
B7 (Inconel)	1.006	B7 (Inconel)	1.006
A193 (Inconel)	1.007	A193 (Inconel)	1.007

ボルトの材料による強度係数の比較		材料	強度係数
材料	強度係数	材料	強度係数
A4-80 (SUS316)	0.42	A4-80 (SUS316)	0.42
B7 (Inconel)	0.19	B7 (Inconel)	0.19
A193 (Inconel)	0.11	A193 (Inconel)	0.11

ねじ規格比較: ねじ規格と強度の相関									
ねじ規格		強度		耐力		ねじ規格		強度	
規格	強度	規格	強度	規格	強度	規格	強度	規格	強度
ISO 2010	8.8	ISO 2010	8.8	ISO 2010	8.8	ISO 2010	8.8	ISO 2010	8.8
ISO 2010	10.9	ISO 2010	10.9	ISO 2010	10.9	ISO 2010	10.9	ISO 2010	10.9
ISO 2010	12.9	ISO 2010	12.9	ISO 2010	12.9	ISO 2010	12.9	ISO 2010	12.9
ISO 2010	15.9	ISO 2010	15.9	ISO 2010	15.9	ISO 2010	15.9	ISO 2010	15.9
ISO 2010	17.8	ISO 2010	17.8	ISO 2010	17.8	ISO 2010	17.8	ISO 2010	17.8
ISO 2010	20.9	ISO 2010	20.9	ISO 2010	20.9	ISO 2010	20.9	ISO 2010	20.9
ISO 2010	22.8	ISO 2010	22.8	ISO 2010	22.8	ISO 2010	22.8	ISO 2010	22.8
ISO 2010	24.7	ISO 2010	24.7	ISO 2010	24.7	ISO 2010	24.7	ISO 2010	24.7
ISO 2010	26.6	ISO 2010	26.6	ISO 2010	26.6	ISO 2010	26.6	ISO 2010	26.6
ISO 2010	28.5	ISO 2010	28.5	ISO 2010	28.5	ISO 2010	28.5	ISO 2010	28.5
ISO 2010	30.4	ISO 2010	30.4	ISO 2010	30.4	ISO 2010	30.4	ISO 2010	30.4
ISO 2010	32.3	ISO 2010	32.3	ISO 2010	32.3	ISO 2010	32.3	ISO 2010	32.3
ISO 2010	34.2	ISO 2010	34.2	ISO 2010	34.2	ISO 2010	34.2	ISO 2010	34.2
ISO 2010	36.1	ISO 2010	36.1	ISO 2010	36.1	ISO 2010	36.1	ISO 2010	36.1
ISO 2010	38.0	ISO 2010	38.0	ISO 2010	38.0	ISO 2010	38.0	ISO 2010	38.0
ISO 2010	40.0	ISO 2010	40.0	ISO 2010	40.0	ISO 2010	40.0	ISO 2010	40.0
ISO 2010	42.0	ISO 2010	42.0	ISO 2010	42.0	ISO 2010	42.0	ISO 2010	42.0
ISO 2010	44.0	ISO 2010	44.0	ISO 2010	44.0	ISO 2010	44.0	ISO 2010	44.0
ISO 2010	46.0	ISO 2010	46.0	ISO 2010	46.0	ISO 2010	46.0	ISO 2010	46.0
ISO 2010	48.0	ISO 2010	48.0	ISO 2010	48.0	ISO 2010	48.0	ISO 2010	48.0
ISO 2010	50.0	ISO 2010	50.0	ISO 2010	50.0	ISO 2010	50.0	ISO 2010	50.0
ISO 2010	52.0	ISO 2010	52.0	ISO 2010	52.0	ISO 2010	52.0	ISO 2010	52.0
ISO 2010	54.0	ISO 2010	54.0	ISO 2010	54.0	ISO 2010	54.0	ISO 2010	54.0
ISO 2010	56.0	ISO 2010	56.0	ISO 2010	56.0	ISO 2010	56.0	ISO 2010	56.0
ISO 2010	58.0	ISO 2010	58.0	ISO 2010	58.0	ISO 2010	58.0	ISO 2010	58.0
ISO 2010	60.0	ISO 2010	60.0	ISO 2010	60.0	ISO 2010	60.0	ISO 2010	60.0
ISO 2010	62.0	ISO 2010	62.0	ISO 2010	62.0	ISO 2010	62.0	ISO 2010	62.0
ISO 2010	64.0	ISO 2010	64.0	ISO 2010	64.0	ISO 2010	64.0	ISO 2010	64.0
ISO 2010	66.0	ISO 2010	66.0	ISO 2010	66.0	ISO 2010	66.0	ISO 2010	66.0
ISO 2010	68.0	ISO 2010	68.0	ISO 2010	68.0	ISO 2010	68.0	ISO 2010	68.0
ISO 2010	70.0	ISO 2010	70.0	ISO 2010	70.0	ISO 2010	70.0	ISO 2010	70.0
ISO 2010	72.0	ISO 2010	72.0	ISO 2010	72.0	ISO 2010	72.0	ISO 2010	72.0
ISO 2010	74.0	ISO 2010	74.0	ISO 2010	74.0	ISO 2010	74.0	ISO 2010	74.0
ISO 2010	76.0	ISO 2010	76.0	ISO 2010	76.0	ISO 2010	76.0	ISO 2010	76.0
ISO 2010	78.0	ISO 2010	78.0	ISO 2010	78.0	ISO 2010	78.0	ISO 2010	78.0
ISO 2010	80.0	ISO 2010	80.0	ISO 2010	80.0	ISO 2010	80.0	ISO 2010	80.0
ISO 2010	82.0	ISO 2010	82.0	ISO 2010	82.0	ISO 2010	82.0	ISO 2010	82.0
ISO 2010	84.0	ISO 2010	84.0	ISO 2010	84.0	ISO 2010	84.0	ISO 2010	84.0
ISO 2010	86.0	ISO 2010	86.0	ISO 2010	86.0	ISO 2010	86.0	ISO 2010	86.0
ISO 2010	88.0	ISO 2010	88.0	ISO 2010	88.0	ISO 2010	88.0	ISO 2010	88.0
ISO 2010	90.0	ISO 2010	90.0	ISO 2010	90.0	ISO 2010	90.0	ISO 2010	90.0
ISO 2010	92.0	ISO 2010	92.0	ISO 2010	92.0	ISO 2010	92.0	ISO 2010	92.0
ISO 2010	94.0	ISO 2010	94.0	ISO 2010	94.0	ISO 2010	94.0	ISO 2010	94.0
ISO 2010	96.0	ISO 2010	96.0	ISO 2010	96.0	ISO 2010	96.0	ISO 2010	96.0
ISO 2010	98.0	ISO 2010	98.0	ISO 2010	98.0	ISO 2010	98.0	ISO 2010	98.0
ISO 2010	100.0	ISO 2010	100.0	ISO 2010	100.0	ISO 2010	100.0	ISO 2010	100.0
ISO 2010	102.0	ISO 2010	102.0	ISO 2010	102.0	ISO 2010	102.0	ISO 2010	102.0
ISO 2010	104.0	ISO 2010	104.0	ISO 2010	104.0	ISO 2010	104.0	ISO 2010	104.0
ISO 2010	106.0	ISO 2010	106.0	ISO 2010	106.0	ISO 2010	106.0	ISO 2010	106.0
ISO 2010	108.0	ISO 2010	108.0	ISO 2010	108.0	ISO 2010	108.0	ISO 2010	108.0
ISO 2010	110.0	ISO 2010	110.0	ISO 2010	110.0	ISO 2010	110.0	ISO 2010	110.0
ISO 2010	112.0	ISO 2010	112.0	ISO 2010	112.0	ISO 2010	112.0	ISO 2010	112.0
ISO 2010	114.0	ISO 2010	114.0	ISO 2010	114.0	ISO 2010	114.0	ISO 2010	114.0
ISO 2010	116.0	ISO 2010	116.0	ISO 2010	116.0	ISO 2010	116.0	ISO 2010	116.0
ISO 2010	118.0	ISO 2010	118.0	ISO 2010	118.0	ISO 2010	118.0	ISO 2010	118.0
ISO 2010	120.0	ISO 2010	120.0	ISO 2010	120.0	ISO 2010	120.0	ISO 2010	120.0
ISO 2010	122.0	ISO 2010	122.0	ISO 2010	122.0	ISO 2010	122.0	ISO 2010	122.0
ISO 2010	124.0	ISO 2010	124.0	ISO 2010	124.0	ISO 2010	124.0	ISO 2010	124.0
ISO 2010	126.0	ISO 2010	126.0	ISO 2010	126.0	ISO 2010	126.0	ISO 2010	126.0
ISO 2010	128.0	ISO 2010	128.0	ISO 2010	128.0	ISO 2010	128.0	ISO 2010	128.0
ISO 2010	130.0	ISO 2010	130.0	ISO 2010	130.0	ISO 2010	130.0	ISO 2010	130.0
ISO 2010	132.0	ISO 2010	132.0	ISO 2010	132.0	ISO 2010	132.0	ISO 2010	132.0
ISO 2010	134.0	ISO 2010	134.0	ISO 2010	134.0	ISO 2010	134.0	ISO 2010	134.0
ISO 2010	136.0	ISO 2010	136.0	ISO 2010	136.0	ISO 2010	136.0	ISO 2010	136.0
ISO 2010	138.0	ISO 2010	138.0	ISO 2010	138.0	ISO 2010	138.0	ISO 2010	138.0
ISO 2010	140.0	ISO 2010	140.0	ISO 2010	140.0	ISO 2010	140.0	ISO 2010	140.0
ISO 2010	142.0	ISO 2010	142.0	ISO 2010	142.0	ISO 2010	142.0	ISO 2010	142.0
ISO 2010	144.0	ISO 2010	144.0	ISO 2010	144.0	ISO 2010	144.0	ISO 2010	144.0
ISO 2010	146.0	ISO 2010	146.0	ISO 2010	146.0	ISO 2010	146.0	ISO 2010	146.0
ISO 2010	148.0	ISO 2010	148.0	ISO 2010	148.0	ISO 2010	148.0	ISO 2010	148.0
ISO 2010	150.0	ISO 2010	150.0	ISO 2010	150.0	ISO 2010	150.0	ISO 2010	150.0
ISO 2010	152.0	ISO 2010	152.0	ISO 2010	152.0	ISO 2010	152.0	ISO 2010	152.0
ISO 2010	154.0	ISO 2010	154.0	ISO 2010	154.0	ISO 2010	154.0	ISO 2010	154.0
ISO 2010	156.0	ISO 2010	156.0	ISO 2010	156.0	ISO 2010	156.0	ISO 2010	156.0
ISO 2010	158.0	ISO 2010	158.0	ISO 2010	158.0	ISO 2010	158.0	ISO 2010	158.0
ISO 2010	160.0	ISO 2010	160.0	ISO 2010	160.0	ISO 2010	160.0	ISO 2010	160.0
ISO 2010	162.0	ISO 2010	162.0	ISO 2010	162.0	ISO 2010	162.0	ISO 2010	162.0
ISO 2010	164.0	ISO 2010	164.0	ISO 2010	164.0	ISO 2010	164.0	ISO 2010	164.0
ISO 2010	166.0	ISO 2010	166.0	ISO 2010	166.0	ISO 2010	166.0	ISO 2010	166.0
ISO 2010	168.0	ISO 2010	168.0	ISO 2010	168.0	ISO 2010	168.0	ISO 2010	168.0
ISO 2010	170.0	ISO 2010	170.0	ISO 2010	170.0	ISO 2010	170.0	ISO 2010	170.0
ISO 2010	172.0	ISO 2010	172.0	ISO 2010	172.0	ISO 2010	172.0	ISO 2010	172.0
ISO 2010	174.0	ISO 2010	174.0	ISO 2010	174.0	ISO 2010	174.0	ISO 2010	174.0
ISO 2010	176.0	ISO 2010	176.0	ISO 2010	176.0	ISO 2010	176.0	ISO 2010	176.0
ISO 2010	178.0	ISO 2010	178.0	ISO 2010	178.0	ISO 2010	178.0	ISO 2010	178.0
ISO 2010	180.0	ISO 2010	180.0	ISO 2010	180.0	ISO 2010	180.0	ISO 2010	180.0
ISO 2010	182.0	ISO 2010	182.0	ISO 2010	182.0	ISO 2010	182.0	ISO 2010	182.0
ISO 2010	184.0	ISO 2010	184.0	ISO 2010	184.0	ISO 2010	184.0	ISO 2010	184.0
ISO 2010	186.0	ISO 2010	186.0	ISO 2010	186.0	ISO 2010	186.0	ISO 2010	186.0
ISO 2010	188.0	ISO 2010	188.0	ISO 2010	188.0	ISO 2010	188.0	ISO 2010	188.0
ISO 2010	190.0	ISO 2010	190.0	ISO 2010	190.0	ISO 2010	190.0	ISO 2010	190.0
ISO 2010	192.0	ISO 2010	192.0	ISO 2010	192.0	ISO 2010	192.0	ISO 2010	192.0
ISO 2010	194.0	ISO 2010	194.0	ISO 2010	194.0	ISO 2010	194.0	ISO 2010	194.0
ISO 2010	196.0	ISO 2010	196.0	ISO 2010	196.0	ISO 2010	196.0	ISO 2010	196.0
ISO 2010	198.0	ISO 2010	198.0	ISO 2010	198.0	ISO 2010	198.0	ISO 2010	198.0
ISO 2010	200.0	ISO 2010	200.0	ISO 2010	200.0	ISO 2010	200.0	ISO 2010	200.0
ISO 2010	202.0	ISO 2010	202.0	ISO 2010	202.0	ISO 2010	202.0	ISO 2010	202.0
ISO 2010	204.0	ISO 2010	204.0	ISO 2010	204.0	ISO 2010	204.0	ISO 2010	204.0
ISO 2010	206.0	ISO 2010	206.0	ISO 2010	206.0	ISO 2010	206.0	ISO 2010	206.0
ISO 2010	208.0	ISO 2010	208.0	ISO 2010	208.0	ISO 2010	208.0	ISO 2010	208.0
ISO 2010	210.0	ISO 2010	210.0	ISO 2010	210.0	ISO 2010	210.0	ISO 2010	210.0
ISO 2010	212.0	ISO 2010	212.0	ISO 2010	212.0	ISO 2010	212.0	ISO 2010	212.0
ISO 2010	214.0	ISO 2010	214.0	ISO 2010	214.0	ISO 2010	214.0	ISO 2010	214.0
ISO 2010	216.0	ISO 2010	216.0	ISO 2010	216.0	ISO 2010	216.0	ISO 2010	216.0
ISO 2010	218.0	ISO 2010	218.0	ISO 2010	218.0	ISO 2010	218.0	ISO 2010	218.0
ISO 2010	220.0	ISO 2010	220.0	ISO 2010	220.0	ISO 2010	220.0	ISO 2010	220.0
ISO 2010	222.0	ISO 2010	222.0	ISO 2010	222.0	ISO 2010	222.0	ISO 2010	222.0
ISO 2010	224.0	ISO 2010	224.0	ISO 2010	224.0	ISO 2010	224.0	ISO 2010	224.0
ISO 2010	226.0	ISO 2010	226.0	ISO 2010	226.0	ISO 2010	226.0	ISO 2010	226.0
ISO 2010	228.0	ISO 2010	228.0	ISO 2010	228.0	ISO 2010	228.0	ISO 2010	228.0
ISO 2010	230.0	ISO 2010	230.0	ISO 2010	230.0	ISO 2010	230.0	ISO 2010	230.0
ISO 2010	232.0	ISO 2010	232.0	ISO 2010	232.0	ISO 2010	232.0	ISO 2010	232.0
ISO 2010	234.0	ISO 2010	234.0	ISO 2010	234.0	ISO 2010	234.0	ISO 2010	234.0
ISO 2010	236.0	ISO 2010	236.0	ISO 2010	236.0	ISO 2010	236.0	ISO 2010	236.0
ISO 2010	238.0	ISO 2010	238.0</						

ねじ規格比較: ねじ規格と強度の相関									
規格	強度	耐力	規格	強度	耐力	規格	強度	耐力	規格
7.9規格									
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10	7.9	10.9	7.9.10
7.9.10	7.9	10.9	7.9.10	7.9					

仕様

商品名	Bumax88 六角ボルト(全ねじ)	規格	ISO 8.8
ボルトサイズ	M6×12	ピッチ	1.0(並目)
頭対辺	10mm	材質	ステンレス鋼 (316L HiMo)
仕様	全ねじ	強度クラス	Class 80
使用温度範囲	−200℃～500℃		

高強度六角ボルト・ナット・ワッシャーが一つずつ入ったエスコオリジナルセット

高強度・高耐食性・高耐熱性・非磁性、高焼付き性

・高強度
SUS304(A2-50)の4倍、SUS316(A4-70)の2倍の耐力

・高耐食
海洋環境下での10年テストでも腐食の発生はなし

・耐熱性
大気中の最高使用温度500℃

抜群の非磁性で各種精密電子機器に使用できます

